


S-Series S-18/S-19

STYLISH DESIGN

AG Neovo S-Series Displays

Made for those who want a stylish award winning display



Elegant & Rugged Design

Smart exterior with exceptional strength



Brilliant Display

Patent pending NeoV Crystal Optic Filter offers superb color definition and image sharpness



Ease Of Use

A host of input options, including analog, S-video and DVI-Digital



Desk/Arm/Wall Flexibility

VESA Compatible LCD display arm or wall mount kit both available



Customer Satisfaction


Global after-sales service, and a 3 year limited warranty

Features
Neo-V Crystal Optic Filter
18"/19" TFT Active Matrix Screen
1280x1024 Resolution
Foldable Small Footprint Stand
Analog, Video & Digital Inputs

AG neovo

A Different Class Of Display

S-Series Displays



NeoV Crystal Optic Filter

Triple coated on both sides, the NeoV Crystal Optic Filter offers anti-glare, anti-reflective properties, while delivering greater color definition.



MVA Technology

Wide angle viewing technology offers greater viewing clarity even when the display is seen from different angles. (S19 only)



Video In Port

Connect DVD, VCR or other video devices directly via a video in port.



DVI-D Port

Take advantage of the latest in technology, by connecting to the DVI-D port for a clearer image.



Auto-Adjustment

Automatically adjusts screen settings for an optimal image, without changing settings manually.



LCD Panel Protection

Protects the LCD panel from potential damage caused by repeated touching of the surface.



OSD

On-Screen Display (OSD) makes adjusting the display settings quick and convenient.



Total Flat Display

A completely flat display, with absolutely no curvature, generates a truer and less distorted view.



LCD Display Arm

Advanced gas-spring suspension guarantees smooth stable operation, and flexibility of use.



Wall Mount Kit

Mount the LCD display on the wall to save even more valuable desktop space.



Security Lock

Increase security by anchoring the LCD display to an immovable object. Compatible with Kensington® security locks.



Specifications

S-18

S-19

| | | | |
|----------------------------------|---|---|---|
| Panel | Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Surface Treatments Viewing Angle (H/V) Display Color Response Time MVA® Technology Frequency Max. Pixel Clock | TFT LCD 18.1" (459.7mm) SXGA 1280 x 1024 0.2805mm 200cd/m ² (Typical) 300:1 (Typical) Hard Coating (3H) & Anti-glare treatment 120°/120° (Minimum) 16.7M 20ms /30ms (Typical) N/A Horizontal: 30kHz - 80kHz Vertical: 50Hz - 75Hz 135MHz | TFT LCD 19.0" (480mm) SXGA 1280 x 1024 0.294mm 250cd/m ² (Typical) 500:1 (Typical) Hard Coating (2H) & Anti-glare treatment 170°/170° (Minimum) 16.7M 15ms /10ms (Typical) MVA® premium Horizontal: 30kHz - 80kHz Vertical: 50Hz - 75Hz 135MHz |
| Inputs | Analog Video Digital | 15-Pin Mini D-Sub 4-Pin Mini Din S-Video RCA Jack CVBS 29-Pin DVI-D | 15-Pin Mini D-Sub 4-Pin Mini Din S-Video RCA Jack CVBS 29-Pin DVI-D |
| Connector | Power | 3-Pin AC Plug | 3-Pin AC Plug |
| NeoV Crystal Optic Filter | Thickness Reflection Rate Transmission Rate Hardness (Moh's Rating) | 2.8mm (0.11") < 1% > 94% > 6H | 2.8mm (0.11") < 1% > 94% > 6H |
| Tilt/Swivel | Tilt Angle / Swivel | 5° ~ 25° (Tilt) | 5° ~ 25° (Tilt) |
| Mounting | VESA FPMPMI | Yes (100mm) | Yes (100mm) |
| Dimensions | Net (W x H x D) Packing (W x H x D) | 436x 426x 200mm (17.2" x 16.8" x 7.9") 550 x 576 x 220mm (21.7" x 22.7" x 8.7") | 436 x 426 x 200mm (17.2" x 16.8" x 7.9") 550 x 576 x 220mm (21.7" x 22.7" x 8.7") |
| Weight | Net Weight Gross Weight | 8.0Kg (17.6lb) 11.1Kg(24.4lb) | 8.2Kg (18.0lb) 11.3Kg(24.9lb) |
| Regulation Approval | Safety & EMI VESA | FCC, UL/CUL, EPA, TUV/GS,CE, NORDIC, TCO95, NUTEK, BSMI, VCCI, CCIB, CB DDC1/2B, DPMS | FCC, UL/CUL, EPA, TUV/GS, CE, NORDIC, TCO95, NUTEK, BSMI, VCCI, CCIB, CB, ISO13406 DDC1/2B, DPMS |
| Power | Power AC Consumption | 100~240V, 50~60Hz < 48W (On), < 5W (Stand-by) < 5W (Off) | 100~240V, 50~60Hz < 48W (On), < 5W (Stand-by) < 5W (Off) |

All specifications are subject to change without prior notice. © 2002 Associated Industries China Inc. The name AG Neovo is a trademark of AIC. All other trademarks are the property of their respective owners.

Optional Accessories



WIRELESS R/F KEYBOARD & MOUSE

LCD DISPLAY ARM

TV TUNER FRAME

WALL MOUNT KIT



A Different Class Of Display

Asia

Associated Industries China, Inc.
10F, No.15, Chi-Nan Road, Sec. 1
Taipei, Taiwan R.O.C.
Tel +886-2-2357-5896
Fax +886-2-3393-2475
marketing@neovo.com
www.neovo.com

Europe

AG Neovo Technology B.V.
Eglantierbaan 8
2908 LV Capelle A/D IJssel
The Netherlands
Tel +31-10-442-57-37
Fax +31-10-442-57-42
service@agneovo.nl
www.agneovo.nl

North America

AG Neovo Technology Corp.
2380 Cume Drive, Suite C
San Jose, CA 95131, USA
Tel +1-408-321-8210
Fax +1-408-321-8211
info@neovo-usa.com
www.neovo-usa.com

Online

Visit www.NEOVO.COM for the latest information on AG Neovo's range of award winning displays.

Dealers Stamp:

