Rechargeable Batteries Sealed lead acid (SLA)

Description

Altronix rechargeable batteries supply 12VDC for security, access, surveillance and fire applications.

Key Features -

- For general purpose, up to 5 years in standby service | Highly efficient, leak proof and maintenance free. or more than 260 cycles at 100% discharge.
- Sealed non-spillable lead acid batteries.

Rechargeable Bateries Reference Chart

Altronix	Output Voltage	A/Hr	Dimensions			Weight	
Model Number			Length	Width	Height	Product	Shipping
BT124	- 12VDC	4	2.76 (70.1mm)	3.5" (88.9mm)	4" (101.6mm)	2.3 lbs. (1.04 kg)	2.8 lbs. (1.27 kg)
BT126		7	2.56" (65mm)	5.94" (150.9mm)	3.66" (93mm)	4.15 lbs. (1.88 kg)	4.65 lbs. (2.11 kg)
BT1212		12	3.75" (95.25mm)	5.94" (150.9mm)	3.5" (88.9mm)	8.3 lbs. (3.76 kg)	8.8 lbs. (4.0 kg)
BT1240		40	6.5" (165.1mm)	7.72" (196.1mm)	6.73" (170.9mm)	26.4 lbs. (12 kg)	27.2 lbs. (12.34 kg)





Rev. Batteries-10232019