

26" LCD Flat Panel Monitors

Features That Make a Difference:

- Multiple inputs (composite video, Y/C, and D-sub computer)
- Superior brightness of 500 cd/m²
- High contrast of 500:1
- Fast LCD response time of 12 ms
- Supports VESA mounting standard (100 mm x 100 mm)
- Available camera and 7-1 media card reader accessory modules
- Supports 1280 x 768 resolution
- Sleek attractive design with hidden controls



American Dynamics™ 26 inch LCD flat panel monitors offer superior brightness, excellent contrast, and high image clarity. The 3D de-interlace function ensures you will experience clear motion quality. Ideal for all CCTV applications, these monitors provide you with multiple inputs/outputs including 2 looping BNC, looping Y/C, 2 looping audio, and D-sub 15 pin connections.

The monitors are excellent for public view applications and offer a remote control, anti-scratch shield, 12 volt power outlet (for camera) and control button lock-out to prevent tampering.

Both models (ADLCD26BX and ADLCD26WX) provide brightness and contrast significantly higher than that of standard LCD monitors.

These flat panel monitors are also ideally suited for use with Intellex® digital video management systems due to matching resolution and superior screen brightness.

Model Numbers

ADLCD26BX26-inch LCD Flat Panel Monitor (black)
ADLCD26WX26-inch LCD Flat Panel Monitor (white)

Accessories

ADMCAMODULE1/3" color DSP CCD varifocal camera,
480 horizontal line, white
ADMCAMOLULEB1/3" color DSP CCD varifocal camera,
480 horizontal line, black
ADMLCD20CARD.Media reader

Mounts

ADMMTLCDPDPLLCD pendant mount with lanyard, black
ADMMTLCDPDPLLCD pendant mount with lanyard, white

General

LCD panel.TFT power management Energy Star compliant
VESA DPMS compatible
Displayable Resolution1280 x 768
Active Area566.4 (H) x 339.84 (V) mm (22.30 x 13.38 in)
LCD Display Color16.7 million (max)
Viewing Angle.85° vertical angle, 85° horizontal angle
Contrast Ratio.500:1
Brightness.500 cd/m²
Response Time.12 ms

Audio

Line Input / outputRCA (X2), speaker (X2) 3.6w
Power Output (Electric).12 VDC output

Electrical

Power Input Voltage100/240 VAC
Consumption126.5W/1.2A max

Mechanical

Dimensions (H x W x D)43.12 x 645.2 x 94.2 x mm (1.69 x 25.40 x 3.70 in)
Unit Weight.12.5 kg (27.55 lb)

Shipping Information

Dimensions (H x W x D)605 x 804 x 265 mm (23.82 x 31.70 x 10.43 in)
Unit Weight.15.5 kg (34.17 lbs)

Environmental

Operating Temperature.-10° to 50°C (14 to 122°F)
Storage Temperature-20° to 60°C (-4 to 140° F)

Inputs/Outputs

1 AnalogVGA (X1) D-Sub 15 pin/ s-video (X1) 4 pin DIN/
Composite (BNC X3, Looping)
Audio Input/outputRCA (X2)/ speaker (X2, 3.6w)

Regulatory

CUL/UL/CE/FCC

Product offerings and specifications are subject to change without notice. Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative. Certain product names mentioned herein may be trade names and/or registered trademarks of other companies.

© 2007 Sensormatic Electronics Corporation. All rights reserved. AD0065-DS-200704-R01-LT-EN

www.americandynamics.net



tyco / Fire & Security