




Premium escutcheon Outside Euro Profile / Inside blind

Product description

- Access decision is made by the AAperio® escutcheon based on access data on card - access data are written on card via EAC system updater
- Can be used with all European (DIN) mortise locks - in wooden, steel and tubular-frame doors
- Main electronics (RFID + radio + BLE) outside - security-relevant electronics inside
- Outside handle rotates freely - inside handle always engaged
- LED for status visualisation

Scope of delivery

- 1 escutcheon with battery (Lithium CR123A) and installation instructions
- Screws, drilling template and tool (for inserting cables)

Technical data - Premium escutcheonMIFARE™
CLASSIC / DESFire™**Approvals**

CE, EN179, EN1906, DIN18273

**Dimension**

312 x 41 x 10/20 mm (H x W x D)

Handle Version

U-Shape

Premium = Higher security version up to grade 3 (EN 1906) with approvals on fire (DIN18273), escape (EN179) route and security

Surface

Stainless steel brushed (ST)

Distance

Distance 72 mm, 92 mm; Spindle 9 mm

Door leaf thickness

Door leaf between 40 and 100 mm thick, in 5 mm increments

Backset

> 40 mm

**Battery**

1 x Lithium CR123A

Battery life

30 openings per day for 49 months

**Radio standard**

IEEE 802.15.4 (2.4 GHz)

Encryption (radio communication)

AES 128 bits

**Class of protection**

IP 54

Operating temperature range

-25°C to 60°C

Relative humidity

< 85% (condensation-free)

**Status**

LED (red/green/orange)

**RFID Technologies (Based on reader type)**

MIFARE Classic® / MIFARE® DESFire® EV1

RFID reading

UID / Sektor / Block / Application / File

RFID Reading range

< 4 cm

**OSS Standard Offline**

Optional available (MIFARE® DESFire®, LEGIC® Advant)