



360



360° fisheye panoramic IR



Built-in AI video and audio analytics and on-device storage



Versatile, robust and sleek, fit for both the hardest outdoor and discreet indoor setups



Factory-installed certificates backed by a trusted platform module (TPM)




Image sensor up to 12MP



Designed and developed in Norway and the UK

Image sensor

12MP

Image sensor size format

1/2.3"

Effective resolution

9MP

Lens

Aperture: $f/2.0$

Fixed focus

Focus distance: 0.5m - ∞

Night vision

Automatic night mode

IR-cut filter

850 nm IR LED

Field of view

>180°

Maximum resolution & Frame rate

3000x3000@30fps

Dynamic range

Multi-exposure line-based HDR

Video compression

H.265, H.264, Motion JPEG

Audio

Microphone array (4x microphones)

AI audio event classification

Audio source localization

Security

Factory-installed certificates, no default passwords, mandatory access authentication, HTTPS/TLS encryption

Network protocols

IPv4, HTTPS, TLS, DNS, mDNS, DNS-SD,

NTP, RTSP, RTP, RTCP, ICMP, DHCP, ARP

Streaming protocols: RTP/UDP, RTP/

RTSP/HTTPS/TCP

Power source

PoE+ (802.3at Type 2)

For installation only: USB-C (1.5A mode)

Power consumption

Typical: 5 W

Max without heater: 12.95 W

Max with heater: 23 W

Storage

MicroSD, SDXC UHS-I

Connection

802.3ab 10/100/1000 Gigabit Ethernet

USB-C for preview and setup

Installation aid

Automatic wall and ceiling detection.

Flexible bracket, mounts to standard back boxes. Refer to technical drawing.

Impact resistance

IK10 (IEC/EN 62262)

Water protection

IP66 (IEC/EN 60529)

Temperature

Operating: -25C to +50C

Storage: -40C to +60C

Heater: 9.6W

Physical characteristics

Dimensions: 152x152x77mm

Weight: 1.1 kg

Body: Aluminum

EMC

EN 55032, EN 61000-3-2/-3, EN 55024, EN 55035, EN61000-6-2/-4, FCC Part 15B, ICES-003 Issue 6

Safety


IEC60950-1, IEC62368-1, IEC60950-22,

UL/CSA60950-1, UL/CSA 62368-1,

UL E164374, NOM-019, IEC62471(IR LED)


Technical drawings

360, side view



Scale 1:2

Mounting bracket, top view



Scale 1:2

| | Designation | Dimension (mm) | Dimension (inch) |
|----------|----------------|---------------------------------|--------------------------------|
| A | Octagon | 62.9 x 62.9 (88.9 diagonal) | 2.47 x 2.47 (3.50 diagonal) |
| B | 4" Square Box | 85.5 x 85.5 (120.9 diagonal) | 3.36 x 3.36 (4.76 diagonal) |
| C | Single Gang | 84.1 | 3.31 |
| D | Double Gang | 84.1 x 46 | 3.31 x 1.81 |
| E | EU Ceiling Box | 70 | 2.76 |
| F | EU Outlet Box | 60 | 2.36 |

Ordering information

Cloud 360

| Product family | PID | Product description |
|----------------|----------|---|
| Cameras | 360-W-30 | Ava Aware Cloud camera - 360 White. 9MP resolution. 30 days retention. AI-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty. |
| Cameras | 360-B-30 | Ava Aware Cloud camera - 360 Black. 9MP resolution. 30 days retention. AI-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty. |
| Cameras | 360-W-60 | Ava Aware Cloud camera - 360 White. 9MP resolution. 60 days retention. AI-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty. |
| Cameras | 360-B-60 | Ava Aware Cloud camera - 360 Black. 9MP resolution. 60 days retention. AI-powered, IR and advanced microphone array, indoor and outdoor, 3 year warranty. |

On-prem Dome

| Product family | PID | Product description |
|----------------|-------|--|
| Cameras | 360-W | Ava 360 Camera White. 9MP resolution. AI-powered pano camera, IR and advanced microphone array, indoor and outdoor, 3 year warranty. |
| Cameras | 360-B | Ava 360 Camera Black. 9MP resolution. AI-powered pano camera, IR and advanced microphone array, indoor and outdoor, 3 year warranty. |

Ordering information

Accessories

| Product family | PID | Product description |
|----------------|---------------|--|
| Cameras | ACC-PEN-CAP-W | Pendant mounting cap for Ava Dome and 360 cameras. White. |
| Cameras | ACC-PEN-CAP-B | Pendant mounting cap for Ava Dome and 360 cameras. Black. |
| Cameras | ACC-MNT-ARM-W | Wall mount arm for Ava Dome and 360 cameras. White |
| Cameras | ACC-MNT-ARM-B | Wall mount arm for Ava Dome and 360 cameras. Black. |
| Cameras | ACC-POL-BRA-W | Pole mount for Ava Dome and 360 cameras. White. |
| Cameras | ACC-POL-BRA-B | Pole mount for Ava Dome and 360 cameras. Black. |
| Cameras | ACC-CRN-BRA-W | Corner mount for Ava Dome and 360 cameras. White. |
| Cameras | ACC-CON-A34-W | Conduit adapter 3/4" for mounting 3/4" NPT or NPS electrical conduits to the camera for cable protection. White. |
| Cameras | ACC-CON-A34-B | Conduit adapter 3/4" for mounting 3/4" NPT or NPS electrical conduits to the camera for cable protection. Black. |
| Cameras | SVCS-CAM-W5YR | 5 year total warranty, with next business day advance replacement. Purchased at the time of original purchase. |