

## LANconnect-S

## **Description**

The LANconnect-S from AXCESS Inc.'s Prism Video line is a dual-input digital video transmitter which allows users to easily add existing cameras to the network. Simply connect two standard CCTV cameras and connect the LANconnect-S to the network. Remote viewing and digital video recording is then facilitated over networks (LAN, WAN or Internet) with virtually any PC.

The LANconnect-S offers interchangeable, on-board CODECs for multiple transmission/compression methods. This unique feature allows users to add the latest technology without having to modify or purchase additional hardware.



## **Features**

**Dual Input** - easily connect two standard CCTV cameras via BNC connectors

**Interchangeable CODEC** - multiple types of video and audio CODECs can be run - allowing for the addition of the latest transmission technology without hardware modification

**TCP/IP Addressable** - addressable by multiple simultaneous receivers (via viewer soft ware or handheld device)

Motion Detection - three distinct regions of interest provide motion-triggered video

Video		Alarm I/O	
Compression	ITU-T H.263, JPEG	Inputs	2 dry contact inputs (12VDC
Performance	2 simultaneous channels:	Outputs	supplied) 2 Form A output contacts,
	H.263 CIF at 100kbps/10fps		24VAC/30VDC/75 mA max per
	CIF 384kbps/15fps		output
	CIF JPEG @ 15fps		Two 4-pin header-type
			connectors, one I/O per pair
			Mechanical
Image Sizes	CIF and QCIF	Size	2" x 5.3" x 8"
Input	2 NTSC/PAL channels (BNC	Weight	1 lbs. 14 oz.
	connector)		
Audio			Environmental
Compression	2 simultaneous channels G.729A	Operating	41° to 113°F (5° to 45°C)
	or G.711	Temperature	
Performance	8-48khz sample rate, 16-bit	Storage	-40° to 158°F (-40° to 70°C)
	sample	Temperature	
Input	2 Line inputs (RCA)	Operational	5% to 95% (non-condensing)
		Humidity	
Output	2 Line outputs (RCA)	Storage	95% at 158°F (70°C)
		Humidity	
Serial Ports			
RS232	Utility port up to 19.2 kb (DB9 connector)		

