

AXIS Camera Station S1132 Recorder

Out-of-the box ready server for UHD surveillance

AXIS Camera Station S1132 Recorder is an out-of-the-box ready rack server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1132 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid-state drive (SSD), AXIS S1132 provides high-performance and reliability for your system.

- > [Ease of installation](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)
- > [5-year warranty](#)



AXIS Camera Station S1132 Recorder

Licenses	32 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	Recording	Qualified for recording up to 48 video channels with a total recording rate up to 384 Mbit per second.
System scalability	Qualified for up to 48 video channels and 96 doors	General	
Hardware		Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 240 GB SSD
Processor	Intel® Core™ i3	Operating conditions	10 °C to 35 °C (50 °F to 95 °F) Humidity 20–80% RH (non-condensing)
Memory	8 GB	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Storage	Hot swappable Enterprise Class HDD Total HDD slot: 4 Free HDD slot: 0 Out-of-the-box storage: 12 TB after RAID 5 Out-of-the-box capacity without RAID: 16 TB (4x4 TB)	Approvals	EMC EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), RCM AS/NZS CISPR 32 Class A, VCCI Class A, KC KN 32 Class A, KC KN 35 Safety IEC/EN/UL 60950-1, EN 62368-1, NOM, BSMI, EAC
RAID	Factory RAID level: 5 RAID levels: 0, 1, 5, 6, 10	Dimensions	596 x 484 x 43 mm (23.47 x 19.06 x 1.7 in), 1U chassis
Power	2 x 350 W hot-plug redundant power supplies (included) (100 - 240 V AC, 50/60 Hz, 4.8 - 2.4 A)	Weight	13.5 kg (29.7 lb)
Connectors	Front side: 1x USB 2.0 Rear side: 2x USB 2.0 2x Ethernet (RJ45) 1 GbE 1x VGA 1x Serial port	Included accessories	Rack rails, 2x C13 to C14 power cords for rack PDU (Wall plug power cords are not included)
Video		Optional accessories	Axis desktop terminals For more accessories, see axis.com
Video streaming	Not intended for local viewing of video. Recommended to use AXIS desktop terminals.	Warranty	5-year warranty, see axis.com/warranty

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility