

AXIS Surveillance Card 64 GB

High endurance microSDXC™ card

AXIS Surveillance Card 64 GB is a high performing edge storage solution optimized for video surveillance. Edge storage enables flexible storage solutions such as de-centralized video recording and may eliminate the need of an onsite server, DVR or NVR. In applications with bandwidth limitations, live video can be viewed in low resolution, while high resolution video is recorded locally on AXIS Surveillance Card 64 GB. Combined with Axis Zipstream technology, even high resolution video can be recorded effectively local on AXIS Surveillance Card 64 GB, both for primary storage or as redundancy for failover recording in case of lost connections.

- > [Optimized for surveillance cameras](#)
- > [Health monitoring ready](#)
- > [SD card adapter included](#)
- > [Axis 3-year warranty](#)



AXIS Surveillance Card 64 GB

SD card		Storage conditions
Form factor	microSDXC™ with SD™ card adapter ^a	-40 °C to 85 °C (-40 °F to 185 °F)
Packaging	The microSDXC™ card and SD™ card adapter are delivered in a jewel case	Sustainability PVC free
Color	White	Approvals EN 55022 Class B, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, RCM AS/NZS CISPR 22 Class B, VCCI Class B
Capacity	64 GB ^b	Compatibility All Axis products with SD card support.
Class	Class 10 (C10) and UHS Speed Class 1 (U1)	Warranty Axis 3-year warranty, see www.axis.com/warranty
Transfer speed read/write	50 – 80 MB/s read/write	a. <i>SanDisk is a trademark of SanDisk Corporation, registered in the United States and other countries. microSDXC and SD marks and logos are trademarks of SD-3C, LLC.</i>
Card dimensions	microSDXC™ card: 15 mm x 11 mm x 1.0 mm (0.59 in x 0.43 in x 0.04 in) SD™ adapter: 24 mm x 32 mm x 2.1 mm (0.94 in x 1.26 in x 0.08 in)	b. <i>1GB=1,000,000,000 bytes. Actual user storage less.</i>
Operating conditions	-25 °C to 85 °C (-13 °F to 185 °F)	Environmental responsibility: axis.com/environmental-responsibility