

XP40-Q1765 Explosion-Protected PTZ Network Camera

PTZ camera for hazardous areas

XP40-Q1765 Explosion-Protected PTZ Network Camera is suitable for onshore, offshore, marine and heavy industrial environments. It features a 316L stainless steel housing certified for hazardous areas according to for example ATEX, IECEx and UL. The housing prevents any inside sparks or explosions from escaping and igniting gases or dust in the surrounding air. XP40-Q1765 provides superb image quality and color fidelity and a high level of flexible integration with other equipment, such as access control and fire alarms. It offers flexible remote accessibility using any existing IP-based networks.

- > **Stainless steel (SAE 316L) and impact resistance**
- > **Continuous 360° pan, ±90° tilt**
- > **Full HDTV 1080p resolution**
- > **18x zoom and autofocus**
- > **Wide temperature range**



XP40-Q1765 Explosion-Protected PTZ Network Camera

Models	XP40-Q1765 XP40-Q1765 -60 C XP40-Q1765 -50 C UL XP40-Q1765 -50 C 110 V UL All models are available in different versions depending on the regional requirements for hazardous equipment certification.	Casing	IP66- and IP67-rated, electropolished SAE 316L stainless steel casing for maximum corrosion protection
Certification part code	XP40-Q1765/XP40-Q1765 -60 C: 1410-25/2420-01 All models supplied in 1410 series explosion-protected housing with 2420 series pan-tilt motor. XP40-Q1765 -50 C UL/XP40-Q1765 -50 C 110 V UL: OXALIS-UL1410-25/UL2420-01	Memory	256 MB RAM, 128 MB Flash
Camera		Power	XP40-Q1765/XP40-Q1765 -60 C/XP40-Q1765 -50 C UL: Max consumption, 24 V AC: 100 W XP40-Q1765 -50 C 110 V UL: Max consumption, 110 V AC: 114 W
Image sensor	Progressive scan RGB CMOS 1/2.9"	Connectors	XP40-Q1765 models: One M25 conduit entry XP40-Q1765 UL models: Two 3/4" NPT conduit entries
Lens	4.7–84.6 mm, F1.6–2.8 Horizontal field of view 59°–4° Vertical field of view 35°–2° Autofocus	Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Day and night	Automatically removable infrared-cut filter	Operating conditions	XP40-Q1765: -40 °C to 70 °C (-40 °F to 158 °F) XP40-Q1765 -60 C: -60 °C to 40 °C (-76 °F to 104 °F) XP40-Q1765 UL models: -50 °C to 70 °C (-58 °F to 158 °F) Humidity 10–100% RH (condensing)
Minimum illumination	Color: 0.5 lux at 30 IRE F1.6 B/W: 0.04 lux at 30 IRE F1.6	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Shutter time	1/28000 s to 2 s	Approvals	EMC EN 55022 Class A, EN 55024 Class A, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, RCM AS/NZS CISPR 22 Class A Safety EN/UL/CSA 60065 Environment IEC/EN 60529 IP66, IP67, IEC/EN 62262 IK10 body, IK08 glass Explosion IEC/EN/SANS/ABNT NBR 60079-0, IEC/EN/SANS/ABNT NBR/GOST 60079-1, IEC/EN/SANS/ABNT NBR/GOST 60079-31, GOST 31610.0, GB3836.1, GB3836.2, CAN/CSA-C22.2 No. 60079-0, CAN/CSA-C22.2 No. 60079-1, CSA-C22.2 No. 60065-03, CAN/CSA C22.2 No. 25, CAN/CSA C22.2 No. 30-M, UL 1203
Pan/Tilt/Zoom	Pan: 360° endless, 0.1 – 45°/s Tilt: ±90°, 0.1 – 24°/s 18x optical zoom and 12x digital zoom, total 216x zoom 64 preset positions, preset accuracy +/-0.1°, Guard Tour, Driver selection, Control queue	Certifications	ATEX: II 2 G Ex db IIC T4 Gb -60°C ≤ Ta ≤ +70°C Gb, II 2 D Ex tb IIIC T135°C Db IP66/67, Certificate: ITS16ATEX101021X IECEx: Ex db IIC T4 -60°C ≤ Ta ≤ +70°C Gb, Ex tb IIIC T135°C Db IP66/67, Certificate: IECEx ITS 15.0068X Inmetro: IIC T4 Gb -60°C ≤ Ta ≤ +70°C Gb, IIIC T135°C Db IP66/67, Certificate: UL-BR 17.0063X cLC CSA: Ex d IIC T4 -60°C ≤ Ta ≤ +60°C, Certificate: 11396-1S-CSA EAC: Ex db IIC T4 Gb -60°C ≤ Ta ≤ +70°C, Ex tb IIIC T135°C Db IP66/67, Certificate: TCRUCGB.ГБ04.В00587 CCOE: Ex db IIC T4 Gb -60°C ≤ Ta ≤ +70°C, Ex tb IIIC T135°C Db IP66/67, Certificate: P400546/1 CNEX: Ex db IIC T4 Gb -60°C ≤ Ta ≤ +70°C, Ex tb IIIC T135°C Db IP66/67, Certificate: 17.1245X IA: Ex db IIC T4 Gb -60°C ≤ Ta ≤ +70°C, Ex tb IIIC T135°C Db IP66/67, Certificate: S-XPL/17.0244X KCC: Ex d IIC T4 -60°C ≤ Ta ≤ +70°C, Ex tD A21 T135°C IP66/67 -60°C to +65°C, Certificate: 17-GA4B0-0351X, 17-GA4B0-0352X UL: Class I, Division 1, Groups B, C, D, T4+ -50°C to +70°C (-58°F to +158°F), Class II, Division 1, Groups E, F, G, IP67, Class 1 Zone 1 A Ex d IIB + Hydrogen T4, Certificate: 20170721-E477542
Video		Dimensions	475 x 512 x 480 mm (18 11/16 x 20 3/16 x 18 7/8 in)
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, and Main profiles Motion JPEG	Weight	50 kg (110 lb)
Resolution	1920x1080 HDTV 1080p to 160x90	Included accessories	Sunshield, installation guide, Windows decoder 1-user license, AXIS Surveillance microSDXC™ Card 64 GB
Frame rate	Up to 30/25 fps (60/50 Hz) in all resolutions	Optional accessories	Ex Power Supply ATEX/IECEX Ex Washer Tank Pressurized ATEX/IECEX, Ex Power Supply UL, Ex Cable ATEX/IECEX/EAC in various lengths, wall and pole stainless steel mounts Not all accessories are available for all certifications. For more accessories, see www.axis.com
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/CBR H.264	Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Image settings	Compression, color, brightness, sharpness, white balance, exposure control, exposure zones, backlight compensation, WDR – dynamic contrast, fine tuning of behavior at low light, rotation, text and image overlay, day/night shift level	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Network		Warranty	Axis 3-year warranty, see www.axis.com/warranty
Security	Password protection, IP address filtering, HTTPS ^a encryption, Digest authentication, User access log, Centralized Certificate Management		
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH		
System integration			
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF® Profile S and ONVIF® Profile G, specification at www.onvif.org		
Analytics	AXIS Video Motion Detection 4, active tampering alarm Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap		
Event triggers	Analytics, Edge storage events		
Event actions	Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap File upload via FTP, SFTP, HTTP, HTTPS network share and email Notification via email, HTTP, HTTPS and TCP		
Data streaming	Event data		
Built-in installation aids	Pixel counter		
General			

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).*

Environmental responsibility:
axis.com/environmental-responsibility