



BCD102SD-ELVS

BCD Entry-Level 1U 2-Bay Rackmount Multi Purpose / Video Recording Server

ENTRY-LEVEL MULTI-PURPOSE 1U 2-BAY RACKMOUNT VIDEO RECORDING SERVER

The entry-level BCD102SD-ELVS offers an affordable and reliable 1U 2-bay rackmount solution for any entry-level deployment. Up to 40TB of raw video-optimized storage is provided by (2) 3.5" 24/7 duty cycle SATA drives.

The BCD102SD-ELVS is powered by an Intel® 9th Generation Core™ processor and has up to 64GB of DDR4 RAM to guarantee fast response times.

System stability and peace of mind is provided with redundant, hot swappable power supplies, an operating system NVMe M.2 solid state drive, and a five-year, on-site, next business day warranty.







KEY FEATURES



Up to 40TB of Raw Storage



Intel® 9th Generation Core™ Processor



256GB OS M.2 Solid State Drive



Windows 10 Pro



M.2 SSD & 24/7 Duty Cycle SATA Drives



Redundant Power



5-Year, On-Site, Next Business Day Warranty





FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993

TECH SUPPORT: support@bcdinc.com





BCD102SD-ELVS

BCD Entry-Level 1U 2-Bay Rackmount Multi Purpose / Video Recording Server

SYSTEM

Operating System

Windows 10 Pro

Memory

Core™ i5-9500/i7-9700k/i9-9900k/ E-2224G: 16GB (2x 8GB) Maximum Configuration: Up to 64GB RAM (4x DDR4 DIMM Slots)

Processor(s)

Intel® 9th Generation Core™ Processor (Up to 8 Cores, 8 Threads, 4.90GHz) Intel® Xeon® E-2224G (4 cores, 4 threads, 3.5GHz)

Processor Passmark

Intel® Core™ i5-9500: 12,109 Intel® Core™ i7-9700k: 17,205 Intel® Core™ i9-9900k: 18,865 Intel® Xeon® E-2224G: 7,466

Networking

(1) 1GbE RJ45 Port, (1) 10GbE RJ45 Port

Expansion Slots

(1) Full-height PCle x16 or (2) Full-height PCle x8 slots
(1) Half-height, Half-length PCle x4 (In default configuration)

USB(s)

Front: (2) USB 3.1 Type A (1) USB 3.1 Type C, Rear: (1) USB 3.1 Type A

Video Outputs

(2) USB 3.1 Type-C (includes 1x USB-C to VGA adapter)

MECHANICAL

Form Factor

1U Rackmount

Power Supply(s)

(2) 550W (100-240VAC) 80 Plus Platinum

Operating Temperature

(Min) 50°F - (Max) 95° F (Min) 10°C - (Max) 35° C

Operating Humidity

10 ~ 85% (non-condensing)

Heat Dissipation

1500 Max BTU/hr

Dimensions (WxDxH)

19" (48.26mm) x 23.19" (58.91mm) x 1.68" (4.28mm)

Max. Weight

27.38 lbs. (12.42 kg)

Warranty

5-Year, On-site, Next Business Day

STORAGE

Hard Drive Bays

(2) 3.5" Bays & (1) M.2 SSD Slots

Hard Drives Supported

PCIe NVMe & SATA

RAID

RAID 0, 1

Maximum Storage

Up to 40TB Raw



FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993

TECH SUPPORT: support@bcdinc.com