



DELL EMC POWERSWITCH N1500 SERIES SWITCHES

Extending enterprise features to small and mid-sized businesses

The N1500 switch series offers a power-efficient Gigabit Ethernet (GbE) network-access switching solution with integrated 10GbE uplinks. With high-performance capabilities and wire-speed performance, utilizing a non-blocking architecture to easily handle unexpected traffic loads, the switches offer simple management and scalability via an 40Gbps (full-duplex) high availability stacking architecture that allows management of up to four switches from a single IP address. An integrated 80PLUS-certified power supply and features such as Energy-Efficient Ethernet and short cable detection provide energy efficiency to help decrease power and cooling costs.

Modernize campus network architectures

Modernize campus network architectures with a power-efficient and resilient 1/10GbE switching solution with Power over Ethernet Plus (PoE+). Select N1500 models offer 24 or 48 ports of PoE+ to deliver clean power to network devices such as wireless access points (APs), Voice-over-IP (VoIP) handsets, video conferencing systems and security cameras.

Leverage familiar tools and practices

All N-Series switches include Dell EMC Networking OS 6, designed for easier deployment, greater interoperability and a lower learning curve for network administrators. One common command line interface (CLI) and graphic user interface (GUI) using a well-known command language gets skilled network administrators productive quickly. With USB auto-configuration, network administrators can rapidly deploy mirrored configurations to numerous devices by simply inserting a USB key.

Deploy with confidence at any scale

N1500 series switches help create performance assurance with a data rate up to 176Gbps (full duplex) and a forwarding rate up to 164Mpps. Scale easily by stacking with 10GbE ports. Switch stacks of up to 200 1GbE ports can be managed from a single screen using the highly available stacking architecture for high-density aggregation with seamless redundant availability. N-Series switches help provide certainty with a lifetime warranty that covers software upgrades, hardware repair or replacement, and optics and cables purchased with the switch.

*Select Networking products carry a Lifetime Limited Warranty with Basic Hardware Service (repair or replacement) for life. Repair or replacement does not include troubleshooting, configuration, or other advanced service provided by Dell EMC ProSupport. For details, visit <https://www.dell.com/en-us/work/shop/networkingwarranty/cp/networkingwarranty>.

Hardware, performance and efficiency

- Up to 48 line-rate GbE RJ-45 ports and four integrated 10GbE SFP+ ports.
- Up to 48 ports of PoE+ with an optional external power supply.
- Up to 200 1GbE ports in a 4-unit stack for high-density, high-availability in IDFs, MDFs and wiring closets.
- Non-stop forwarding and fast failover in stack configurations.
- Energy-Efficient Ethernet and lower power PHYs reduce power to inactive ports and idle links, providing energy savings from the power cord to the port.
- Fresh Air compliance for operation in environments up to 113°F (45°C) helps reduce cooling costs in temperature-constrained deployments.

Deploying, configuring and managing

- USB auto-configuration rapidly deploys the switch without setting up complex TFTP configurations or sending technical staff to remote offices.
- Management via an intuitive and familiar CLI, embedded web server (GUI), SNMP-based management console application (including Dell EMC OpenManage Network Manager), Telnet or serial connection.
- Private VLAN extensions and Private VLAN Edge support.
- AAA authorization, TACACS+ accounting and RADIUS support for comprehensive secure access support.
- Authentication tiering allows network administrators to tier port authentication methods such as 802.1x, MAC Authentication
- Bypass and Captive Portal in priority order so that a single port can provide flexible access and security.
- Layer 3 Lite IPv4 and IPv6 functionality including static routing and Routing Information Protocol support.
- Remote Switch Port Analyzer (RSPAN) monitors ports across a Layer 2 domain without costly dedicated network taps.

Product	Description
N1500 series	N1524: 24x RJ45 10/100/1000Mb auto-sensing ports, 4x SFP+ ports, 1 integrated 40W PSU N1524P: 24x RJ45 10/100/1000Mb PoE+ (up to 30.8w) auto-sensing ports, 4x SFP+ ports, 1 integrated 600W PSU (requires C15 plug) N1548: 48x RJ45 10/100/1000Mb auto-sensing ports, 4x SFP+ ports, 1 integrated 100W PSU N1548P: 48x RJ45 10/100/1000Mb PoE+ (up to 30.8w) auto-sensing ports, 4x SFP+ ports, 1 integrated 600W PSU (requires C15 plug)
Power cords	C13 to NEMA 5-15, 3M C13 to C14, 2M C15 to NEMA 5-15, 2M (C15 for POE N-Series only)
Power supplies (optional)	RPS720 external power supply for N1500 non-POE (720 watts): N1524 and N1548 (sold separately) MPS1000 external power supply for N1500 PoE+ switches (1000 watts): N1524P and N1548P (sold separately)
Optics (optional)	Transceiver, SFP, 1000BASE-T Transceiver, SFP, 1000BASE-SX, 850nm wavelength, up to 550m reach Transceiver, SFP, 1000BASE-LX, 1310nm wavelength, up to 10km reach Transceiver, SFP, 1000BASE-ZX, 1550nm wavelength, up to 80km reach Transceiver, SFP+, 10GbE, SR, 850nm wavelength, up to 300m reach Transceiver, SFP+, 10GbE, LR, 1310nm wavelength, up to 10km reach Transceiver, SFP+, 10GbE, ER, 1550nm wavelength, up to 40km reach
Cables (optional)	Dell Technologies Networking cable, SFP+ to SFP+, 10GbE, copper twinax direct

Technical specifications

Physical

4 integrated front 10GbE SFP+ dedicated ports, 2 10GbE can be used as stacking ports
USB (Type A) port for configuration via USB flash drive
Auto-negotiation for speed and flow control
Auto MDI/MDIX, port mirroring
Flow-based port mirroring
Broadcast storm control
Energy-Efficient Ethernet per port settings
Redundant variable speed fans
Air flow: I/O to power supply
Integrated power supply: 40W AC (N1524), 100W AC (N1548), 600W AC (N1524P, N1548P)
RJ45 console port with RS232 signaling (RJ-45 to female DB-9 connector cable included)
Dual firmware images on-board
Switching engine model: Store and forward

Chassis

Size (1RU, H x W x D):
N1524 and N1548: 1.7 in x 17.3 in x 10.1 in (43.2 mm x 440.0 mm x 257.0 mm)
N1524P and N1548P: 1.7 in x 17.3 in x 15.2 in (43.2 mm x 440.0 mm x 387.0 mm)
Approximate weight: 6.6lbs/3kg (N1524), 12.8lbs/5.8kg (N1524P), 8.8lbs/4kg (N1548), 15.4lbs/7kg (N1548P)
Rack mounting kit with 2 mounting brackets, bolts and cage nuts

Environmental

Power supply efficiency: 80% or better in all operating modes
Max. thermal output (BTU/hr): 103.1 (N1524), 297.2 (N1524P), 152.2 (N1548), 582.4.3 (N1548P)
Power consumption max (watts): 30.2 (N1524), 87.1 (N1524P), 44.6 (N1548), 170.4 (N1548P)
Operating temperature: 32° to 113°F (0° to 45°C)
Operating humidity: 95%
Storage temperature: -40° to 149°F

(-40° to 65°C)

Storage relative humidity: 85%

Performance

MAC addresses: 16K
Static routes: 256 (IPv4)/128 (IPv6)
Dynamic routes: 256 (IPv4)
Switch fabric capacity: 128Gbps (N1524 and N1524P) (full duplex); 176Gbps (N1548 and N1548P)
Forwarding rate: 128Mpps (86 Gbps) N1524 and N1524P
164Mpps (110 Gbps) N1548 and N1548P
Link aggregation: 64 LAG groups, 144 dynamic ports per stack, 8 member ports per LAG
Priority queues per port: 8
Line-rate Layer 2 switching: All (non-blocking)
Line-rate Layer 3 routing: All (non-blocking)
Flash memory: 256MB
Packet buffer memory: 1.5MB
CPU memory: 1GB
RIP routing interfaces: 128
VLAN routing interfaces: 128
VLANs supported: 512
Protocol-based VLANs: Supported
ARP entries: 2,048 (IPv4)/512 (IPv6)
NDP entries: 400
Access control lists (ACL): Supported
MAC and IP-based ACLs: Supported
Time-controlled ACLs: Supported
Max number of ACLs: 100
Max ACL rules system-wide: 2,048
Max rules per ACL: 1,023
Max ACL rules per interface (IPv4): 1,023 (ingress), 1,023 (egress)
Max ACL rules per interface (IPv6): 512 (ingress), 509 (egress)
Max VLAN interfaces with ACLs applied: 24

IEEE compliance

802.1AB LLD
Dell Voice VLAN
Dell ISDP (inter-operates with devices running CDP)

802.1D Bridging, Spanning Tree
802.1p Ethernet Priority (User Provisioning and Mapping)
Dell Adjustable WRR and Strict Queue Scheduling
802.1Q VLAN Tagging, Double VLAN Tagging, GVRP
802.1S Multiple Spanning Tree (MSTP)
802.1v Protocol-based VLANs
802.1W Rapid Spanning Tree (RSTP)
Dell RSTP-Per VLAN (compatible with Cisco's RPVST+)
Dell Spanning tree optional features: STP root guard, BPDU guard, BPDU filtering
Network Access Control, Auto VLAN
802.1X Logical Link Control
802.2 10BASE-T
802.3 Gigabit Ethernet (1000BASE-T)
802.3ab Frame Extensions for VLAN Tagging
802.3ac Link Aggregation with LACP
802.3ad 10 Gigabit Ethernet (10GBASE-X)
802.3ae PoE+ (N1524P and N1548P)
802.3at LAG Load Balancing
802.3AX Energy Efficient Ethernet (EEE)
802.3az Fast Ethernet (100BASE-TX) on Management Ports
802.3u Flow Control
802.3z Gigabit Ethernet (1000BASE-X)
ANSI LLDP-MED (TIA-1057)
MTU 9,216 bytes

RFC compliance and additional features

General Internet protocols

General Internet protocols are supported. For a detailed list, please contact your Dell Technologies representative.

General IPv4 protocols

General IPv4 protocols are supported. For a detailed list, please contact your Dell Technologies representative.

General IPv6 protocols

General IPv6 protocols are supported. For a detailed list, please contact your Dell Technologies representative.

Layer 3 functionality

1058	RIPv1
2082	RIP-2 MD5 Auth
1724	RIPv2 MIB Extension
2453	RIPv2

Multicast

2932	IPv4 MIB
4541	IGMP v1/v2/v3 Snooping and Querier
IEEE 802.1ag draft 8.1-	Connectivity Fault Management

Quality of service

2474	DiffServ Field
Dell Flow Based QoS	
2475	DiffServ Architecture Services Mode
2597	Assured Fwd PHB (IPv4/IPv6)
Dell	L4 Trusted Mode
Dell	Port Based QoS (TCP/UDP) Services Mode
Dell	UDLD

Network management and security

1155	SMIPv1	2295	Transport Content Negotiation
1157	SNMPv1	2296	Remote Variant Selection
1212	Concise MIB Definitions	2346	AES Ciphersuites for TLS
1213	MIB-II	2576	Coexistence Between SNMPv1/v2/v3
1215	SNMP Traps	2578	SMIPv2
1286	Bridge MIB	2579	Textual Conventions for SMIPv2
1442	SMIPv2	2580	Conformance Statements for SMIPv2
1451	Manager-to-Manager MIB	2613	RMON MIB
1492	TACACS+	2618	RADIUS Authentication MIB
1493	Managed Objects for Bridges MIB	2620	RADIUS Accounting MIB
1573	Evolution of Interfaces	2665	Ethernet-like Interfaces MIB
1612	DNS Resolver MIB Extensions	2674	Extended Bridge MIB
1643	Ethernet-like MIB	2737	ENTITY MIB
1757	RMON MIB	2818	HTTP over TLS
1867	HTML/2.0 Forms with File Upload Extensions	2819	RMON MIB (groups 1, 2, 3, 9)
1901	Community-based SNMPv2	2863	Interfaces MIB
1907	SNMPv2 MIB	2865	RADIUS
1908	Coexistence Between SNMPv1/v2	2866	RADIUS Accounting
2011	IP MIB	2868	RADIUS Attributes for Tunnel Prot.
2012	TCP MIB	2869	RADIUS Extensions
2013	UDP MIB	3410	Internet Standard Mgmt. Framework
2068	HTTP/1.1		
2096	IP Forwarding Table MIB		
2233	Interfaces Group using SMIPv2		
2246	TLS v1		
2271	SNMP Framework MIB		

3411	SNMP Management Framework	4716	SECSH Public Key File Format
3412	Message Processing and Dispatching	6101	SSL
3413	SNMP Applications	Dell	Enterprise MIB supporting routing features draft-ietf-hubmib-etherif-mib-v3-00.txt (Obsoletes RFC 2665)
3414	User-based security model	Dell	LAG MIB Support for 802.3ad
3415	View-based control model	Dell	802.1x Monitor Mode
3416	SNMPv2	Dell	Custom Login Banners
3418	SNMP MIB	Dell	Dynamic ARP Inspection
3577	RMON MIB	Dell	IP Address Filtering
3580	802.1X with RADIUS	Dell	Tiered Authentication
3737	Registry of RMOM MIB	Dell	RSPAN
4086	Randomness Requirements	Dell	OpenFlow 1.3
4113	UDP MIB	Dell	Python Scripting
4251	SSHv2 Protocol	Dell	Support Assist
4252	SSHv2 Authentication	Dell	HiveManager NG
4253	SSHv2 Transport		
4254	SSHv2 Connection Protocol		
4419	SSHv2 Transport Layer Protocol		
4521	LDAP Extensions		

Regulatory, environment and other compliance

Safety and emissions

Australia/New Zealand: ACMA RCM Class A
Canada: ICES Class A; cUL
China: CCC Class A; NAL
Europe: CE Class A
Japan: VCCI Class A
USA: FCC Class A; NRTL UL; FDA 21 CFR 1040.10 and 1040.11
Eurasia Customs Union: EAC
Germany: GS mark
Product meets EMC and safety standards in many countries inclusive of USA, Canada, EU, Japan, China. For more country-specific regulatory information and approvals, please see your Dell Technologies representative.

RoHS

Product meets RoHS compliance standards in many countries inclusive of USA, EU, China, and India. For more country-specific RoHS compliance information, please see your Dell Technologies representative.

EU WEEE
EU Battery Directive
REACH

Energy

Japan: JEL
Certifications (available or coming soon)
Available with US Trade Agreements Act (TAA) compliance.
N-Series products have the necessary features to support a PCI-compliant network topology.



Dell Technologies Services

Plan, deploy, manage and support your IT transformation with our top-rated services

Consulting

Dell Technologies Consulting Services provides industry professionals with a wide range of tools and the experience you need to design and execute plans to transform your business.

Deployment

Accelerate technology adoption with ProDeploy Enterprise Suite. Trust our experts to lead deployments through planning, configuration and complex integrations.

Management

Regain control of operations with flexible IT management options. Our Residency Services help you adopt and optimize new technologies and our Managed Services allow you to outsource portions of your environment to us.

Support

Increase productivity and reduce downtime with ProSupport Enterprise Suite. Expert support backed by proactive and predictive artificial intelligence tools.

Education

Dell Technologies Education Services help you develop the IT skills required to lead and execute transformational strategies. Get certified today.

Learn More at bcdvideo.com/dell-networking or by contacting sales@bcdinc.com