

Specifications:

| | |
|------------------------------|---------------------------------------|
| <i>Image Sensor</i> | <i>1/3" Sony Super HAD II CCD</i> |
| <i>Effective Pixel</i> | <i>768Hx494V</i> |
| <i>Resolution</i> | <i>Color 600 TVL</i> |
| <i>Mini. Illumination</i> | <i>Color: 0.03lux, Mono 0.001 lux</i> |
| <i>Shutter Speed</i> | <i>1/60 ~ 1/100,000</i> |
| <i>Scanning System</i> | <i>2:1 Interlaced Scanning</i> |
| <i>Sense Up</i> | <i>Max 128x</i> |
| <i>S/N Ratio</i> | <i>More than 48 dB</i> |
| <i>Digital Wide Dynamic</i> | <i>WDR Adjustable</i> |
| <i>Privacy Zone</i> | <i>4 areas</i> |
| <i>AGC</i> | <i>On/Off</i> |
| <i>BLC</i> | <i>48 zones</i> |
| <i>Motion Dections</i> | <i>48 zones</i> |
| <i>Digital Zone</i> | <i>128x</i> |
| <i>DNR</i> | <i>2D/3D Optional</i> |
| <i>Sync</i> | <i>Internal</i> |
| <i>AWB</i> | <i>Manual/Auto/Auto Tracking</i> |
| <i>Reverse Function</i> | <i>Horizontal/Vertical</i> |
| <i>Power Supply</i> | <i>12VDC/24VAC 2.5W</i> |
| <i>Operating Temperature</i> | <i>-14°F - 131°F</i> |
| <i>Storage Temperature</i> | <i>-40°F - 150 °F</i> |

Actual Product(s) may vary from photo. All specifications may change without notice.



BC7109

Features:

- **Image Sensor:** 1/3" Sony Super HAD II CCD
- **Wide Dynamic Range**
- **3D Digital Noise Reduction**
- **Mini.. Illumination:** Color 0.03lux, Mono 0.001 lux
- **Sense-up Star Light Technology 128x**
- **48 areas motion detection with multi area settings**
- **48 areas black light compensation**
- **OSD menu control, privacy mask mode**
- **Mechanical IR Cut Filter**
- **Dual Voltage 12VDC/24VAC**

