RF3334 Series Keyfobs

www.boschsecurity.com





- Uniquely coded arm and disarm buttons
- Panic alarm
- LED indicator
- Programmable option buttons

The RF3334 Series Keyfobs includes the RF3334 and the RF3334E. The RF3334 transmits at a frequency of 304.00 MHz while the RF3334E transmits at 433.42 MHz. Both models are wireless and have four buttons. Each model allows you to arm and disarm the security system or send a panic alarm. Programmed with a unique code, each model works exclusively with your compatible security system. Two option buttons are user-defined to perform additional functions.

Functions

Panic Alarm

The RF3334 Series can send a panic code to your monitoring company if your security system is programmed to do so. Press both the lock and unlock buttons simultaneously for two seconds to send a panic alarm.

LED Indicator

The LED flashes to indicate a signal was sent to your security system.

Programmable Option Buttons

The RF3334 Series can be programmed to control additional devices in your protected area. Two option buttons are available. Possible programming choices include turning on lights or opening the garage door.

Certifications and approvals

Region	Certification	
Europe	CE	RF3334E: 1999/5/EC, EN60950 1992 (2nd edition) +A1 (1993) +A2 (1993) +A3 (1995) +A4 (1997), EN55022-1 Class B (1999), EN55024 (1998), EN50130-4 (1995) +A1 (1998) +A2 (2003), EN61000-4-2 (1995), EN61000-4-3 (1997), EN61000-4-4 (1995), EN61000-4-5 (1995), EN61000-4-6 (1997), EN61000-4-8 (1994), EN61000-4-11 (1994), EN301489-3 (2000), ETS300683 (1997), EN300222-1 (1997-99), EN300220-3 (1997-99)
USA	FCC	RF3334: ESV-0407-2
Canada	IC	RF3334: 12491021155
Brazil	ANATEL	RF3334E: 1361-05-1855

Installation/configuration notes

Compatibility Information

Model	Receivers	Control Panels
RF3334	RF3212	Solution Ultima 844, 862, and 880, CC488

	RF3213	VR-8
	RF3222	DS7400XiV4
	RF3224	DS7240, DS7220, D6412, and D4412
RF3334E	RF3212E	Solution Ultima 844, 862, and 880, CC488
	RF3213E	VR-8
	RF3222E	DS7400XiV4
	RF3227E	DS7240, DS7220, D6412, and D4412
	RF3228E	Marise
	RF3249E	DA (Abacus)

Recommended Batteries

The following battery types are recommended for correct operation of your keyfob: Duracell® DL2025, Eveready® CR2025, or Panasonic® CR2025.

Technical specifications

Environmental Considerations

Relative Humidity:	0% to 95% (non-condensing)
Temperature (operating):	-29°C to +65°C (-20°F to +150°F) For UL listed requirements, the temperature range is 0°C to +49°C (+32°F to +120°F)

Mechanical Properties

Dimensions: 3.8 cm x 6.3 cm x 1.3 cm (1.5 in. x 2.5 in. x 0.5 in.)

Power Requirements

Batteries:	Two 3 VDC lithium batteries
Battery Life:	5 to 6 years under normal operating conditions with recommended battery types

Transmission Characteristics

Frequency	
RF3334:	304.00 MHz
RF3334E:	433.42 MHz

Trademarks

 $\mathsf{Duracell}^{\circledast}$ is a registered trademark of the Gillette Company, USA, in the United States and/or other countries.

Eveready[®] is a registered trademark of Eveready Battery Company, Inc.

 $\mathsf{Panasonic}^{\circledast}$ is a registered trademark of Matsushita Electric Industrial Co., Ltd.

Ordering information

RF3334 Four-Button Wireless Key Fob (304 MHz) Wireless, four-button key fob Order number **RF3334**

RF3334E Four-Button Wireless Key Fob (433.42 MHz) Wireless, four-button key fob Order number RF3334E

Represented by:

Americas:

Americas: Bosch Security Systems, Inc. 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 280 0096 Fax: +1 585 223 9180 security.sales@us.bosch.com www.boschsecurity.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002

P.O. Box 80002 5617 BA Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

@ Bosch Security Systems 2013 | Data subject to change without notice 2571380363 | en, V1, 01. Oct 2013

Asia-Pacific:

Asia-Pacific: Robert Bosch (SEA) Pte Ltd, Security Systems 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2609 apr.securitysystems@bosch.com www.boschsecurity.asia

China:

China: Bosch (Shanghai) Security Systems Ltd. 201 Building, No. 333 Fuquan Road North IBP Changning District, Shanghai 200335 China Phone +86 21 22181111 Fax: +86 21 22182398 www.bacsbecurity.com.cn www.boschsecurity.com.cn

America Latina:

America Latina: Robert Bosch Ltda Security Systems Division Via Anhanguera, Km 98 CEP 13065-900 Campinas, Sao Paulo, Brazil Phone: +55 19 2103 2860 Fax: +55 19 2103 2862 Iatam.boschsecurity@bosch.com www.boschsecurity.com