



General Specifications

| | | |
|-----------------------|-----------------|------------------------------------|
| Power Requirement | - VDC regulated | 7-16 VDC |
| Current Consumption | - Average | 45ma |
| | - Peak | 135ma |
| Card Read Range | - Metric | 20mm - 40 mm |
| | - USA | 0.8" - 1.6" |
| Operating Temperature | - Metric | -25°C to +65°C |
| | - USA | -13°F to +149°F |
| Relative Humidity | - % max | 90%, operating non condensing |
| Reader Dimensions | - Metric | 90mm (L) x 90mm (W) x 20mm (D) |
| | - USA | 3.54" (L) x 3.54" (W) x 0.79" (D) |
| Status LED's | - Colour | Green and Red |
| Audible Tone | | Internal & external buzzer control |
| Colour finish | | Charcoal |
| Certifications | | C-tick, FCC, CE |
| IP Rating | | IP65 |
| ROHS | | Compliant |

M1000

Robust, Reliable, Security
 – built to withstand harsh environments.

The BT815S (slim) readers is a very low profile (20mm, 0.79"), extremely robust unit and has been engineered to withstand the harshest of environments. The BT815S is designed with ease of installation in mind and may be installed on flush surfaces and mounted on most international standard gang boxes with the addition of a backing plate.

Available in several models, the BT815S caters for all security requirements large or small and offers a solution for all applications whether driven by budget or functionality.

Model Features

| Model | Technology | | | Authentication Factors | | Encode | | | | Encryption | | | | Sector Keys | | | 13.56MHz Credential type and option | | | | Output Protocol | | | Other | | | | | | |
|---------|----------------|-------------|---------|------------------------|-----------|--------|---------|--------|-------------|------------|------------------|----------|-------------|-------------|----------------|----------|-------------------------------------|--------------|-----------|-----------|-----------------|---------------------|---------------------|----------------|--------------------|------------------|--------------|------------------|---------------|---|
| | Mifare Classic | Mifare Plus | DESfire | Card | Biometric | Keypad | CSN/UID | Sector | Application | Random UID | Diversified Keys | Crypto 1 | Mifare Plus | 3 DES | AES (optional) | MiPASS 2 | MiPASS 3 | Customisable | ISO14443A | ISO14443B | Mifare 1K & 4K | Mifare Plus 2K & 4K | DESfire EV1 4K & 8K | Wiegand 32 BIT | Wiegand 26-199 BIT | Encrypted RS485* | Read / Write | Indoor / Outdoor | Tamper option | |
| BT815-2 | ✓ | | | ✓ | | | ✓ | ✓ | | | ✓ | ✓ | | | ✓ | | | | ✓ | ✓ | | | | ✓ | | | ✓ | ✓ | | |
| BT815-3 | ✓ | | | ✓ | | | ✓ | ✓ | | | ✓ | ✓ | | | | | ✓ | ✓ | ✓ | ✓ | | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| BT815-4 | | | ✓ | ✓ | | | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | | | ✓ | | | ✓ | ✓ | | | ✓ | ✓ | | | ✓ | ✓ | | |
| BT815-6 | ✓ | ✓ | ✓ | ✓ | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

* Requires High Security Module (HSM) AES 128bit encryption