



FEATURES:

- Versatile display formats provide a convenient user interface with 2x2 or 3x3 multi-screen display
- Sequential camera display
- · Specific display sequencing
- Spot monitor can disply any live camera in the full-screen format with camera title
- On-screen display includes date, time, alarm status, video loss and camera titles
- PIP (Picture-in-Picture) display with one inset
- Individual dwell settings
- · Live, VCR, and Preview modes
- Freeze button freezes what is displayed on the monitor
- Single/multiple alarms
- VCR mode alarm
- Video loss alarm
- RS-232 or RS-485 interface
- Rack mountable (brackets included)
- 3 Year Warranty

CPT-MD9

9-Channel Duplex Monochrome Multiplexer



Distributed by:



1-800-722-CCTV

Please contact your local representative for additional information.

CPT-MD9 9-Channel Duplex Monochrome Multiplexer













Specifications:

Video Input	1 Vp-p, 75 Ohm Camera input: 9 (BNC)
Video Output	1 Vp-p, 75 Ohm Looping output: 9 EA (BNC) SPOT output: 1 EA (BNC) MAIN output: 1 EA (BNC) High Resolution: 512x464 pixels with 256 level gray scale
VCR In/Out	1 Vp-p, 75 Ohm, 1 EA BNC
Alarm	DB-25S Female Alarm input: 9 EA Alarm output: 1 EA (NC/NO/COMMON) Alarm hold time: 20 sec. default; menu selectable to 0-99 seconds
Buzzer	On/Off selectable
Input power	12VDC, 1.5A
Remote Control	DB-25S Female RS-232 RS-485
Ambient Temperature	32°F to 95°F 0°C to 35°C
Ambient Humidity	10% to 90% (non-condensing)
Dimensions W x H x D	17 x 1.75 x 12.25 (in) 432 x 44 x 310 (mm)
Net Weight	6.2 lbs 2.8 kg

www.capturecctv.com (



1-800-471-2003

CPT0101