

FS-mmW-1 mmWave Fall Sensor

Innovational Fall Detection to Protect Loved Ones




Climax's FS-mmW-1 mmWave Fall Sensor is a new 60GHz millimeter-wave (mmWave) Technology fall detection sensor, which differs from the previous pendant-wearing fall detection method. Since mmWave Technology is capable of determining the people's distance range, velocity and angle of fall arrival, FS-mmW-1 mmWave Fall Sensor comes with higher accuracy and speed when detecting the motions of falling.

MmWave Technology is powered by its advanced radar-based presence detection algorithm, which can accurately detect human movement, capturing even subtle human movements. Climax's FS-mmW-1 mmWave Fall Sensor also provides high quality in challenging indoor environment, including in darkness. Moreover, it is enhanced with pet immunity, eliminating blind spot to minimize false alarm situation.

This sensor is suitable for various types of people, such as the elders or disabled people. Recommended installed locations include nursing homes, hospitals, homes or community facility areas. Climax's FS-mmW-1 mmWave Fall Sensor can be installed in corners of each frequently visited place such as bathroom, bedroom, kitchens or many areas where people may easily fall down, therefore ensuring accidents of the loved ones can be assisted at the earliest timing possible.



- Millimeter-wave Fall Detection Technology
- Radar-based Presence Detection Algorithm
- Fall Detection in Darkness



FS-mmW-1 mmWave Fall Sensor



■ Support for detection range up to 5 m x 5 m



■ Accurately detecting the movement of falling, suitable for application in various locations.

Features

- Accurate fall detection capability
- Non-wearable sensing system
- Pet immunity function
- Corner-mounted
- Low battery detection
- IPX4 waterproof protection
- IR lens for power saving
- LED indicator
- Support for supervision signal

Specifications

FS-mmW-1

mmWave RF Frequency	60 to 64 GHz
Power Source	AC Power 5V/2A
Backup Battery	Li-ion Polymer 3.7V/800mAH
Mounting Options	Wall-mounted
Waterproof Protection	IPX4
Adaptive Detection Range	5 m x 5 m
Detection Angle	Right: 45° Left: 45° (total 90°)
Operating Temperature	0°C to 45°C (32°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	137 mm x 77 mm x 31 mm

* Note: Actual battery life may vary with product settings, operating environment, and usage patterns.

Ordering Information

FS-mmW-1 mmWave Fall Sensor