

Cylinders and Padlocks

Euro Cylinders Euro Cylinders

Application:

The eCLIQ® cylinder is available in a wide range of cylinder applications including euro (double or single), rim, mortice, padlocks, and more.

Specification:

- Temperature range: -25°C - 85°C
- Encrypted (AES) communication between cylinder and key/c-key
- Available in a variety of finishes
- Minimum length: 28 mm (Euro model)
- Modular (from 30mm, by 5 or 10mm extensions)
- Maintenance-free up to 200,000 cycles (includes integrated lubricant reserve)
- Power supplied via the eCLIQ® key's embedded battery



Standards:

- IP54 (dust and rain protection cap available for one or both sides - IP55)
- EN 1303/DIN 18252

Finish:

Satin Nickel
Other finishes available on request

Variants:

Code	Description
AA-E-N530-SN	eCLIQ Double Euro CLIQ/CLIQ 30/30mm
AA-E-N531-SN	eCLIQ Double Euro CLIQ/Mechanical 30/30mm
AA-E-N532-SN	eCLIQ Single Euro 30mm
AA-E-N534-SN	eCLIQ Euro Cylinder and Turn 30/30mm
AA-E-SGL-5	eCLIQ Single Extensions 5mm
AA-E-SGL-10	eCLIQ Single Extensions 10mm
AA-E-SGL-15	eCLIQ Single Extensions 15mm
AA-E-SGL-20	eCLIQ Single Extensions 20mm
AA-E-SGL-25	eCLIQ Single Extensions 25mm