



# FLASHLOCK® PADLOCK

Email or Text a Key for Access in a Flash



- » No Bluetooth® to Pair and No App Required
- » FlashLock Padlock uses Serial Optical Communications Technology Combined with a Web Browser to Issue and Receive keys



**Communications**  
Infrared Key Fob Available



**IP68 Rating**  
-4° to 140° F; -20° to 60° C  
Water Resistant



**Indicators**  
LED Indicator Lights

**FlashLock Padlock is IP68 Rated, Making it Ideal for Unpredictable Climates**

- » **Control Who Enters What Space at What Time**
- » **Grant Temporary or Ongoing Access**
- » **Conveniently Adjust Permissions Anytime**



## FlashLock® Padlock

Part Number: FL-PL02

CAW	Version 8.0	Version 9.0 (or newer)
Enterprise	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Basic	<input type="checkbox"/>	<input type="checkbox"/>

FlashLock is a keyless lock that facilitates access control using any web-enabled device.

### Specifications

<b>Physical</b>	Brass and Stainless Steel
<b>Operating Temperatures</b>	-4° to 140° F, -20° to 60° C Below 14° F (-10° C) battery capacity is significantly reduced
<b>Dimensions</b>	6.055" L x 2.24" W x 1.5" H (153.78 mm x 56.9 mm x 38.1 mm)
<b>Weight</b>	35.7 oz (1012 g)
<b>Power</b>	EL123 lithium battery, field replaceable
<b>Visual Indicators</b>	Four LED indicator lights
<b>Access Options</b>	Serial optical with web device, IR with fob, Encoder I/O, CK-FLASH, CK-AIR2
<b>Management Options</b>	Encoder I/O
<b>Software</b>	CyberAudit® Enterprise 9.0 (or newer) with FlashLock SEM, or myflashlock.com
<b>Battery Life</b>	Up to 1 year
<b>Audit Capacity</b>	Up to 11,000 open/lock events

