

Outdoor Surveillance Junction Box


Certified to IP66 and to IK10




- All-aluminum Shell
- Aesthetic Design, Easy Installation
- Tamper Alarm with Optional Alarm Switch
- IP66 Ingress Protection and IK10 Vandal Resistance
- Compatible with DH-PFA153 Heavy-duty Pole Mount, Dahau PTZ Dome Camera Wall Mounts, and MNVR/MXVR Mobile Recording Devices

Technical Specifications			Dimensions (mm/in.)	
			Dimensions (mm/m.)	
Material	Alu	ninum and SECC		
Dimensions		0 mm x 365.0 mm x 191.0 mm 72 in. x 14.37 in. x 7.52 in.)	1122/110460 1122/10400 1222/10400 1222/10400 1040000 104000 1040000 1040000 1040000 1040000 1040000 10400000000	
Weight	9.0	kg (19.84 lb)		
Load Bearing Capacity				
Front	10.	kg (22.05 lb)	70.7 [2.78"]	
Side	6.0	kg (13.23 lb)	84.0 [3.31"] 365.0 [14.37"]	
Inside	5.0	kg (11.02 lb)		
Color	Wh	te		
Operating Temperature		-40° C to 60° C (-40° F to 140° F)		
Humidity		o 90% RH		
Environmental				
Ingress Protection				
Vandal Resistance			Applications	
Installation	Wa	Mount or Pole Mount	n	
Compatibility		 DH-PFA153 Heavy-duty Pole Mount Dahau PTZ Dome Camera Wall Mounts Dahua MNVR and MXVR Mobile Recording Devices 		
Ordering Information				
Туре	Part Number	Description		
Junction Box	DH-PFA143	Outdoor Surveillance Junction Box, IP66, IK10		

175.0 [6.89 6.0 [02:20"] Ø70.0 [Ø2.76°] 48.1 [1.89*] 4-0100 (00.39") 70.0 [2.76*]





Rev 001.002 © 2020 Dahua Technology USA. All rights reserved. Design and specifications are subject to change without notice

IK10