

Wall Mount Bracket



- Stainless Steel Construction
- Compatible with DH-PSDW81642M-A360

Overview

Dahua's Wall Mount Brackets work with front-end services to support installation methods such as wall mounting, pole mounting, corner mounting, and in-ceiling mounting. Select brackets are designed to suit challenging environments such as those with high temperatures and humidity, frequent vibrations, and highly-corrosive materials. These reliable brackets work in temperatures ranging from $-40\text{ }^{\circ}\text{C}$ to $+60\text{ }^{\circ}\text{C}$ ($-40\text{ }^{\circ}\text{F}$ to $+140\text{ }^{\circ}\text{F}$) and in relative humidity of less than 90%.

Technical Specification

Structure

Casing Material	SUS304 Stainless Steel
Product Dimensions (L x W x H)	386.8 mm x 161.5 mm x 116.5 mm (15.23 in. x 6.36 in. x 4.59 in.)
Net Weight	3.30 kg (7.28 lb)
Gross Weight	3.95 kg (8.71 lb)
Load Bearing	40.0 kg (88.19 lb)
Screw Thread Type	G1-1/2
Packaging Dimensions (L x W x H)	386.8 mm x 161.5 mm x 116.5 mm (15.23 in. x 6.36 in. x 4.59 in.)

Environment

Operating Temperature	$-40\text{ }^{\circ}\text{C}$ to $+60\text{ }^{\circ}\text{C}$ ($-40\text{ }^{\circ}\text{F}$ to $+140\text{ }^{\circ}\text{F}$)
Operating Humidity	< 90% (RH)
Storage Temperature	$-40\text{ }^{\circ}\text{C}$ to $+60\text{ }^{\circ}\text{C}$ ($-40\text{ }^{\circ}\text{F}$ to $+140\text{ }^{\circ}\text{F}$)
Storage Humidity	10% to 90% (RH)
Anti-corrosion Level	Basic Protection

Ordering Information

Type	Part Number	Description
Accessory	DH-PFB710W-SG	Wall Mount Bracket, Silver-grey

Dimensions

