



Thermal Imaging Camera

Industry temperature measurement

TEi Series

160×120 Uncool FPA detector

Low cost, CCD Came, rarotatable LCD

50Hz realtime measurement, portable



TEi Series Portable Thermal Imaging Camera

TEi series is not only an affordable IR camera, it also combine the traits of economical and practical. With its 2.8" LCD rotatable screen and JPEG storage, the camera symbolizes easy-to-use, standard and professional, developing for those applications that need instant infrared troubleshooting in power plant, petrochemicals, scientific research, fire fighting, and building inspection, metallurgy, etc.



Parameter

	Item	TEi	TEi-P	
Detector characteristics	Detector type	Uncooled FPA microbolometer		
	Array size/format	160x120		
Image characteristics	Field of view/min focus distance	12° x 9°/0.3m		
	Spatial resolution (IFOV)	1.3mrad		
	Thermal sensitivity	≤0.1°C@30°C		
	Frame rate	60Hz	50/60Hz	
	Focus	Manual		
	Electronic zoom	N/A	2X	
	Spectral range	8-14μm		
	Built-in visual camera	300,000 pixels, CCD full screen thermal image display		
Image display	LCD	High-resolution color 2.8" LCD		
Measurement	Temperature ranges	-20°C~+350°C	-20°C~+350°C, extendable to +600°C	
	Accuracy	± 2 °C or ± 2% of reading, Whichever is greater		
	Measurement correction	Automatic/manual		
	Measurement mode	Movable spot, Movable area (maximum, minimum and average temperatures). Isotherm. Alarm (voice, color)	Up to 4 movable spots. Up to 3 movable areas (maximum, minimum and average temperatures). Line profile. Isotherm. Temperature difference. Alarm(voice, color)	
	Color palette	3	11	
	Image adjustment	Auto/manual gain and brightness		
	Setup functions	Date/time, temperature unit, language		
	Emissivity correction	Variable from 0.01 to 1.0		
	Atmospheric transmission correction	Automatic corrections according to user input		
	Storage card	Built-in flash memory, Up to 1000 images	Built-in flash memory, SD card (1G), Up to 4000 images	
Image storage	Storage mode	Manual single image saving	Automatic/manual single image saving	
	File format-thermal	JPEG, 14 bit thermal image with measurement data		
	File format-visual	JPEG		
	Voice annotation	N/A	Input via built-in microphone Up to 40 seconds of digital voice per image stored with image	
Laser pointer	Laser pointer	Class 2, 1mw/635nm(red)		
Power supply	Battery type	Li-Ion, rechargeable		
	Battery operating time	3 hours continuous operation		
	Charging system	Intelligent charger	Intelligent charger or power supply adaptor (optional) online charge	
	Power saving	YES		
	External power	10-15V DC		
	Operating temperature	-15°C- +50°C		
Environment	Humidity	≤90%non-condensing		
	Encapsulation	IP54		
	Weight	0.7Kg		
Physical characteristics	Dimensions	197mmx178mmx73mm		
	External DC input	Yes		
Interface	Audio output	N/A	Yes	
	Video output	N/A	PAL/NTSC	
	SD card	N/A	Yes	
	USB	Image (thermal and visual), measurement data transfer to PC	Image (thermal and visual), measurement data and voice transfer to PC	

▲ The information contained in this document is subject to change without notice



Rotatable LCD



Laser Pointer
CCD Camera



Manual focus



One key operation



Shortcut key



Low power consumption,
3 hours continuous operation




SD card

USB

Audio output

Video output

Power connector



Line measurement



Area measurement



Optional Lenses