

3 GALLIFORD ROAD INDUSTRIAL ESTATE HEYBRIDGE MALDON ESSEX CM9 4XD

TEL: MALDON (01621) 856850 FAX: MALDON (01621) 856162 Email: dantech@dantech.uk.com Website: www.dantech.uk.com

PRODUCT DATA SHEET FOR DA371

PRODUCT DESCRIPTION

A power supply with 1 x 1.5 Amp 12V DC (13.7) output, which will house and charge one VRLA battery up to 7Ah capacity. This unit comes with two SPCO relays that provide Mains Fail and Low Voltage monitoring. Typical uses are for powering door access controllers, electric releases, maglocks and CCTV cameras.

PRODUCT SPECIFICATION

General Electrical and Mechanical Specification

•	Supply Voltage:	240V AC 50Hz
•	Current Consumption:	< 50VA at full load
•	Colour:	White
•	Size in mm (W x H x D):	210 x 260 x 80
•	Weight in Kg:	2.8
•	Packed Size in mm (W x H x D):	218 x 280 x 83
•	Packed Weight in Kg:	2.9
•	Case Material:	1.2 mm Powder coated Mild Steel
•	Operating Temperature:	10 to +40°C
•	Storage Temperature:	20 to +50°C
•	Operating Relative Humidity:	up to 95% non condensing
•	MTBF:	50,000 hours
•	CE approved:	Yes

Other Relevant Specification

•	Output Voltage:	12V DC (nominal 13.7V DC)
•	Current:	
•	Mains Fail Indication:	Yes
•	Low Volts Indication:	Yes
•	Recommended Battery Size:	7Ah
•	Fan Cooled:	No
•	Tamper Switch:	Yes