
# DATACARD® SP35 PLUS CARD PRINTER







# **Convenient card printing**

The SP35 Plus card printer is designed for easy operation and maintenance. User-friendly features include:

- A printer driver that provides message prompts, recovery instructions, color image previews and online user help
- Driver support for Microsoft®
  Windows® 2000, XP and
  Windows Vista® operating systems
- Quick-change supplies
- Operator-replaceable printheads
- Front-facing input and output card hoppers
- Small, efficient design
- Continuous card cleaning

# CONVENIENT DESIGN, EXCELLENT EASE OF USE

The Datacard® SP35 Plus card printer delivers everything you need to print vivid, one-sided cards. With its productive print speed, superb image quality and easy operation, this convenient printer is ideal for issuing education, healthcare and staff IDs — and more.

- Exceptional productivity. The SP35 Plus card printer personalizes up to 160 full-color cards or 750 one-color cards per hour. This printer is also extremely light and portable, weighing only nine pounds. Its sleek design and compact size make it a welcome addition to any desktop.
- Superb edge-to-edge imaging. The SP35 Plus card printer leverages Advanced Imaging Technology™ to produce vivid and vibrant full- or one-color photos, graphics and text across the entire card surface. This exclusive technology uses optimized print ribbons and user-adjustable controls to yield smooth, uniform and solid backgrounds, improved color matching with image capture devices, enhanced bar code printing and sharp reproduction of edges and fine text.
- Multiple options and capabilities. In addition to standard bar code printing, the SP35 Plus card printer gives you the option to integrate magnetic stripe encoding and smart card personalization with a factory option or simple field upgrade. So, you can purchase these printers with confidence, knowing you can upgrade your card printing capabilities at any time.





The Datacard® SP35 Plus card printer offers an ideal mix of convenience and simplicity in an attractive, compact model.

# **DATACARD®** SP35 PLUS CARD PRINTER

#### Standard features

# Print capabilities

One-sided edge-to-edge printing Continuous-tone, full-color, black-and white photos Alphanumeric text, logos and digitized signatures Variety of bar codes Background patterns Printer pooling

#### Advanced Imaging Technology™ Print speed

Full-color printing: Up to 160 cards per hour One-color printing: Up to 750 cards per hour

### Capacity

Input hopper: 100 cards, 0.03 in. (0.76mm) Output hopper: 20 cards, 0.03 in. (0.76mm)

#### Connectivity

Bi-directional USB

#### Printer driver

User-adjustable image and color controls Stand-alone driver diagnostics Color image and test card preview Online user help Add text, image or pattern to topcoat Supply usage tab

# User-friendly operation

Audible and visual message prompts Automatic card feed Operator-replaceable printhead Continuous cleaning roller Easy-access components including quick-change ribbon cartridges Highly accessible card path

#### Datacard® Certified Supplies featuring Intelligent Supplies Technology

Automatic identification and validation for ribbons Automatic printer settings Low ribbon warning Ribbon saver

#### Warranties

24-month standard depot warranty 24-month printhead warranty (no pass restrictions)

# **Options**

# Magnetic stripe encoding

ISO: IAT or NTT Dual high- and low-coercivity Tracks I, 2 and 3 (I track for NTT)

#### Smart card personalization

Contact/contactless all-in-one reader Contact PC USB Reader Contact station

Clear card personalization Input hopper empty detection Soft-sided carrying case

### **Specifications**

# Physical dimensions

L 16.5 in. × W 7.8 in. × H 9.0 in. (41.25 cm × 19.5 cm × 22.5 cm)

### Weight

8 to 9 lbs (3.6 kg to 4.1 kg) depending on options

#### Print resolution

300 dots per inch, 256 shades

#### Electrical requirements

100/120V, 50/60 Hz 220/240V, 50/60 Hz

#### Plastic cards accepted

ISO ID-1/CR-80 size cards 3.370 in. x 2.125 in. (85.6 mm x 53.98 mm) PVC with glossy laminate surface Clear cards Other core materials with PVC overlaminates are optional

#### Card thicknesses accepted

0.009 in. to 0.055 in. (0.2286 mm to 1.397 mm)

# Operating environment

60°F to 95°F (15°C to 35°C) 20% to 80% non-condensing humidity

# Storage environment

5°F to 140°F (-15°C to 60°C) 10% to 90% humidity

#### Operating system support

Microsoft® Windows Vista®, Windows® XP, Windows® 2003 Server, and Windows® 2008 Server supported on printer driver version 4.0 Windows® 2000 supported by printer driver version 2.0 Datacard® Open Platform printer driver for non-Windows platforms

#### Agency approvals

UL, cUL, FCC, CE, CCC, Ctick, RoHS

# **Datacard**Group

11111 Bren Road West

Minnetonka, MN 55343-9015

+1 952 933 1223

www.datacard.com

DP9-9007

Datacard, Intelligent Supplies Technology and Advanced Imaging Technology are registered trademarks, trademarks and/or service marks of DataCard Corporation in the United States and/or other countries. Microsoft, Windows, and Windows Vista are registered trademarks of Microsoft Corporation. Names and logos on sample cards are fictitious. Any similarity to actual names, trademarks or tradenames is coincidental

©2007-2009 DataCard Corporation. All rights

Specifications subject to change without notice.