

Eagle Eye Camera DF03

Indoor/Outdoor 12MPix Fisheye, POE, IR



The Eagle Eye Camera DF03 delivers 12MP high resolutions images with a 360 degree view. This indoor/outdoor 12MP fisheye with integrated microphone and IR provides clear 360 degree view day and night. The camera works in concert with Eagle Eye Cloud VMS dewarping to produce panoramic, split panoramic, ePTZ, and 2+1 ePTZ images. Dewarping can also be configured on the camera.

Key Features

- > 12 Mega Pixel
- > 360 Degree View
- > Integrated Microphone
- > Indoor/Outdoor Rated
- > Fixed Aspherical lens with Distortion Correction
- > Digital Wide Dynamic Range
- > Night Vision Smart IR, 15m range

Dimension Drawing

| Camera | |
|-----------------------------|--|
| Pixels | 12 Mega Pixel |
| Resolutions | 4000×3000 @20fps, 2560x2560/1800x1800/ 1440x1440/960x960 @25/30fps |
| Lens | 1.83mm |
| Night Vision | IR LEDs up to 15m |
| Field of View | 180°x180° |
| Dynamic Range | DWDR |
| Digital Noise Reduction | 2D/3D DNR with defog |
| Digital Image Stabilization | Automatic |
| Applications | Best for medium size open areas, hallway intersections, lobbies, and retail. |
| Image Sensor | 1/1.7" progressive scan CMOS |
| Iris | Fixed F2.4 |
| Shutter Speed | 1/5s to 1/20000s |
| Min Illumination | Color 0.009Lux; IR ON 0 Lux |

| Digital Capabilities | |
|----------------------|---|
| Video Compression | H.265, H.264, and MJPEG |
| Audio Compression | G.711, RAW_PCM |
| Image Settings | Rotation, Saturation, Brightness, Contrast, Sharpness |
| Dewarping | Internal or via Eagle Eye Cloud VMS |

| Setup | |
|---------------------|---|
| Eagle Eye Cloud VMS | Preconfigured with secure password, plug and play |
| Camera Settings | Fully Integrated with Eagle Eye Cloud VMS |
| Cyber Secure | Eagle Eye Verified |

| Interface | |
|--------------|--|
| Ethernet | Waterproof RJ-45 Female 10/100 Base-T |
| Audio | 1Ch audio in, 1Ch audio out or built in Microphone |
| Alarm | 1Ch Output, 1Ch Input |
| Edge Storage | Micro SD/SDHC/SDXC slot, Max 128GB |

| Physical/Power | |
|-----------------------|--|
| Power | DC12V/Power Over Ethernet (IEEE 802.3af) |
| Power Consumption | 5W IR Off, 9W IR On |
| Operating Temperature | -40°C to +60°C (working temperature) |
| Operating Humidity | 0% - 90% RH |
| Waterproof | IP66 |
| Approvals | CE/FCC |
| Dimensions | Ф 130 x 38.3mm |
| Weight | 500 grams |
| Housing | Aluminum |

| Eagle Eye Part Numbers | |
|------------------------|--|
| EN-CDUF-003a | Eagle Eye Camera DF03 Indoor/Outdoor Fisheye 12MP IR, IP66, 1.83mm Lens, POE |
| EN-RRC02 | Eagle Eye Camera+ Rapid Replacement |
| EN-CABX-004 | Eagle Eye Camera Junction Box BX004 (WA03,PE02,DF03) |