

FNR-4004/500

Home | Security | Recording | NVRs

FNR-4004/500
Network Video Recorder, 4xIP,
1600x1200 (@ 2 Channels), H.264, 500GB, 12VDC

Art-Nr. 93035



Main Features

Up to 4 IP video channels	High security with Linux Embedded operating system
Video compression H.264	Bit rate up to 8Mbps max.
Resolution up to 1600x1200@25fps (2 cameras)	Easy installation - Plug&Play
Maximum recording speed 100fps	Various splits for live cameras
Client management software, web browser access	Supports megapixel cameras
Server-client architecture	Up to 2TB internal storage capacity

Specifications

Series	eneo F
IP channels	4
Video inputs (amount)	-
Compression standard	H.264
Max. recording resolution	1600 x 1200
Max. recording rate	100 B./Sek., @ 704 x 576
Recording speed	up to 25 fps per channel
Image quality control	1600x1200@25fps (2 channels), 1600x1200@12fps (2 channels), 1280x720@25fps (2 channels), 704x576@25fps (4 channels), 640x480@25fps (4 channels)
Operation mode	Triplex
Storage media	internal: 1x SATA
Harddisk capacity (internal)	500 GB
Max. harddisk capacity (internal)	2 TB

FNR-4004/500

(Continuation Specifications)

Main video outputs	1x VGA, CVBS
Monitor outputs	VGA, 1Vp-p, (C)VBS, 75ohms, BNC
Spot monitor	no
Remote access	remote software, browser
Recording	alarm, contact, movement, timer, permanent
Alarm inputs	4
Alarm output	1
Pre-alarm recording	up to 30sec.
Secondary Storage	MP4
Displays	-
Network	10/100 Base-Tx, RJ45
Network protocols	PPPoE, DHCP, DNS, DDNS, NTP, SADP, SNMP, TCP/IP, SMTP
Network connection	RJ-45
Control units (external)	remote control, mouse
Serial interfaces	RS-485
Interfaces external storage	2x USB 2.0
Remote configuration	via web browser, remote software
Password protection	yes
Supply voltage	12VDC
Intergrated writer	no
Firmware update	USB Flash drive, via remote software
Supported network suppliers	eneo F series
ONVIF	no
Dimensions (HxWxD)	315x44.5x230mm
Weight	2.5 kg (without HDDs)
Parts supplied	PSU, Quick Installation Guide, Manual and Software on CD-ROM, installation CD, mouse, battery, IR remote controller
Certificates	CE

Optional accessories

92714	FXC-1302/W	1/3" Network Camera, Day&Night, H.264, WiFi, 1600x1200, 12VDC, PoE, ONVIF
92711	FXD-1001/IR	1/3" Network Dome, Fixed, Day&Night, 2.7 -9mm, 1280x960, infrared, PoE, ONVIF
92709	FXD-1002/IR	1/3" Network Dome, Fixed, Day& Night, 2.7 -9mm, 1600x1200, infrared, PoE, ONVIF
92715	FXC-1201M	1/3" Network Camera, Day&Night, H.264, CS/C, 1600x1200, 24VAC/12VDC, PoE
92713	FXC-1302	1/3" Network Camera, Day&Night, H.264, MPEG4, 1600x1200, 12VDC, PoE, ONVIF

FNR-4004/500

93172	FINITRA	Video Management Software, for eneo F-Series
92712	FLC-1301	1/3" Network Camera, Day&Night , 640x480, H.264, MPEG4, MJPEG , 12VDC, PoE, ONVIF
92739	FXC-1201/V8W	1/3" Network Camera, Day&Night, 3-8mm, H.264, 1600x1200, Wall Mount, ONVIF
92717	FXD-1102	1/3" Network Dome, Fixed, Day&Night, 4mm , 1600x1200, vandal resistant, ONVIF
92716	FLD-1101	1/4" Network Dome, Fixed, Day&Night, 4mm , 640x480, vandal resistant, PoE, ONVIF
92742	FXC-1201/V50W	1/3" Network Camera, Day&Night, 5-50mm, H.264, 1600x1200, Wall Mount, ONVIF



VIDEOR