eneo®

GL CMS-MANAGER

Article-No.: 92547

Viewer and Control Software for eneo
Network Series GL, MJPEG, MPEG4, H.264

Mainfeatures

Efficient, stable and fast network accessibility	Administration of arbitrarily many video sources
Simultaneously viewing of up to 16 cameras	Full image function
User groups with individual layouts	Continuous, scheduled, alarm & motion record modes
Multiple search functions for record events	Software set up & programming via network
Arbitrary access on live pictures	Supports MJPEG, MPEG-4 & H264 standard recording

Specifications

Software Categorie	Video Management
Series	eneo GL
Operation system	Windows XP
On-screen display	4 MB VGA card capable of 24 bit true colour display neccessary
Hardware recommendation (CPU)	Core2Duo (16 cameras), P4 2.8GHz
Hardware recommendation (HD capacity)	120 GB
Hardware recommendation (RAM)	512 MB
Hardware requirement (CPU)	Core2Duo (16 cameras), P4 3.4GHz
Hardware requirement (HD capacity)	60 GB
Hardware requirement (RAM)	512 MB
Licensing type	n/a
Licensing method	unlimited
Demo version	n/a
Languages (client)	German, English, French, Italian, Spanish, Turkish, Russian
Support of mobile units	n/a
Alarm management	Siren, alarm in and output
Alarm management	yes

Specifications (continued)

Control units (external)	mouse, keyboard
Multi monitor operation	no
PTZ support	yes
Recording settings	choosable per channel
Recording functions	time triggered, permanent, motion detector, contact
Supported network suppliers	eneo
Supported video sources	network camera, network encoder
Managable video sources max.	unlimited
Product training	available

Your partner for eneo products: