

GLS-2104

Home | Security | IP Server/Decoder | Servers

GLS-2104

Network 4-channel Video Server, PAL,

1-chann. Audio, Ethernet, 12VDC

Art-Nr. 91555



Main Features

4-ch. Video Networking Server for LAN/WAN/Internet
MJPEG Compression
Surveillance via LAN/WAN and Internet (w./o. PC)
Image Frame Rate: Up to 25 Fr./Sec. (352x288 Px.)
1-ch. Audio Transmission
RS-485 Telemetry Control Interface

Alarm In / Outputs and Motion Detection
Integrated Web Server: 10Base-T/100Base-TX
Viewer for Monitoring, Recording and Configuration
Pre and Post Event Recording (in Client PC)
E-Mail Notification in Case of an Alarm

Specifications

Series	eneo GL
System	PAL
System requirements	Processor: Pentium IV, Core2 Duo; 2.8GHz; 512MB RAM; Microsoft Windows XP, Vista
Compression standard	MJPEG
Ethernet interface	10Base-T, 100Base-TX, RJ-45
Network protocols	TCP/IP, DHCP, HTTP, FTP, SMTP, SNMP, DDNS, UPnP, PPPoE
Power over Ethernet	no
Configuration	Via WebBrowser, Built-in WebServer
Picture adjustments	Color, Brightness, Contrast (via Network)
Data rate	up to 2.0MB/sec.
Resolution max.	704 x 272
Video resolution	Mux Mode: 704x272; Quad Mode: 352x288 (CIF), 176x144 (QCIF)
Image transm. rate max.	25 B./Sek.

GLS-2104

(Continuation Spezifications)

Frame rate	Mux Mode: 12.5 Fps x 4 (704x272); Quad Mode: 25 Fps x 4 (352x288 & 176x144)
Video inputs (amount)	4
Video inputs	4x 1Vp-p, (C)VBS, 75ohms, BNC
Video output	1Vp-p, CVBS, 75ohms, BNC
Audio support	yes
Audio input	1x line-in
Alarm inputs	yes, 4x for NO/NC contacts
Alarm output	1x Relais NO/NC contact
PTZ Support	yes
Activity detection	yes
Internal storage	no
Digital storage media	SD card: 32MB ~2GB. Recording as JPEG Snapshots / AVI Files
Access	10 Users simultaneous support
Serial interfaces	RS-485
Software upgrade	SD card / USB / FTP
Password protection	yes
Supply voltage	12VDC
Power consumption	6.0watts
Housing	Aluminium
Colour	Beige
Temperature range (Operation)	0 ~+50°C
19" Rack mountable	no
Weight	approx. 1.0kg
Parts supplied	PSU 230VAC, USB connection cable, 16-channel Viewer S/W, Programming CD-Rom, Manual
Management Software Support	Aimetis - Symphony, Zelarip IP, NetAvis, GL-Manager, Milestone XProtect Corporate
Certificates	CE

Optional accessories

76056	ZELARIS_IP S04E	Software Extension for Zelarip_IP S04 for further 4 Cameras, max. 64 Cameras
76003	ZELARIS_IP VC	Client Version for Zelarip_IP Server for one Workstation
76053	ZELARIS_IP S04	Server/Client Video Management Software Basic Version, 4 Camera Server license
76051	ZELARIS_IP V04	Video Management Software for Standalone Systems, Basic Version, 4 Cameras
76001	ZELARIS V08	Digital Video Network Crosslink, 8 Inputs, not Extentable, USB 2.0 Dongle

GLS-2104

76002	ZELARIS V16	Digital Video Network Crosslink, 16 Inputs, not Extentable, USB 2.0 Dongle
76058	ZELARIS_IP HL-E	Extension for Control Room Client for further up to 1024 Channels max.
76047	ZELARIS_IP HL-B	Control Room Client Software, Basic Version, Up to max. 1024 Channels

