

GLS-2302H

Home | Security | IP Server/Decoder | Servers

GLS-2302H

Network Server, Video, Audio, 1 Channel, H.264,

MPEG-4, MJPEG, 12VDC, PoE, ONVIF

Art-Nr. 92708



Main Features

1 channel video/audio server for LAN/WAN

Resolution 720 x 576 max.

Simultaneous video streaming (H.264/MJPEG/MPEG-4)

USB connector for configuration

Shared access (up to 10 simultaneously)

Up to 3 password levels

Integral motion detection

Audio and alarm input and outputs

Alarm-recording (Micro SD card/SDHC)

ONVIF conformity

Privacy zone masking

Client management software included

Specifications

Series	eneo GL
Video encoding/decoding	720x576 Full D1, 352x288 CIF, 176x144 QCIF. GOP structure: I (MP=0), IP (M=1), IPB (M=2), IBB (M=3) "Low latency" mode, Field/Frame based coding, selectable frame rate: 1-50/60 Fields/sec.
Compression standard	H.264, MPEG-4, MJPEG
Web browser	MS Internet Explorer vers. 7.0 or higher, Netscape version 4.5 min., Google Chrome (Java), Mozilla Firefox (Java), Safari (Java)
Ethernet interface	10Base-T, 100Base-TX, RJ-45
Network protocols	3GPP, IPv4, DHCP, HTTP, HTTPS, DDNS, UPnP, DNS, FTP, SMTP, SMTP, RTSP, UDP, TCP
Configuration	via web browser
Picture adjustments	colour, brightness, contrast
Stream types	H.264, MPEG-4, MJPEG multiple
Frame rate	Max. 25 frames/sec.

GLS-2302H

(Continuation Spezifications)

Resolution max.	720 x 576
Image transmission rate max.	25 B./Sek.
Video inputs (amount)	1
Audio support	yes
Audio In-/Output	1/1 two-way audio streaming
Motion detector	96 areas, 5 levels
Audio input	1x Line-in 3Vp-p, approx. 50kohms
Audio output	line output
Alarm inputs	yes
Alarm processing	alarm triggered by build-in motion detection, external alarm. Alarm notify to ANNP, e-mail, FTP, SD card, alarm out
Alarm output	Open Collector (5V / 0.02A max.)
PTZ support	yes
Activity detection	yes
Internal storage	SD card
Pre-alarm recording	1 to 10sec.
Post-alarm recording	1 to 10sec.
Access	10 users simultaneous support
Serial interfaces	no
Firmware update	via network
Menu languages	German, English, French, Italian, Dutch, Spanish, Swedish, Finnish, Hungarian, Czech, Polish, Portugese, Russian, Turkish, Chinese
Password protection	yes, 3 password levels
Power over Ethernet	yes, IEEE 802.3af
Supply voltage	12VDC, PoE
Management Software Support	GL-Manager, Zelaris (limited)
ONVIF	core specifications 1.01
Certificates	CE
19" Rack mountable	no
Dimensions (HxWxD)	34x80x94
Temperature range (operation)	0°C ~+45°C
Special features	installation wizard via web browser



VIDEOR