



IAM-5SE1004MUP

Article number: 221889

Gigabit Switch, Unmanaged 60W, 4x PoE, Industrial Design -40°C~+75°C, PD port

Gigabit PoE Switch, DIN Rail

Up to 30W per port, total max. 120W

4x 10/100/1000 PoE Ports, IEEE 802.3ab/af/at/u

PoE watchdog (reboot automatically)

Gigabit Uplink Ports 1xRJ45, 1xSFP

Surge protection IEC61000-4-5 (6KV)

1 x RJ45 10/100/1000 PoE In Port (60W PoE Input)

Temperature range -40° C ~ +75° C

Specifications

Features:	
Multicast compliant	no
Port mirror	no
QoS	no
SNMP	no
Network:	
Ethernet Standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3ab 1000BaseT, IEEE 802.3x Flow Control, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE)
Internal switching capacity (Mpps)	8,9 Mpps
Internal switching capacity (Gbit/s)	12 Gbps
VLAN	yes
Interfaces / Inputs / Outputs:	
Ethernet interface	10Base-T, 100Base-TX, 1000Base-T
Ports	4x 10/100/1000Base-T, 1x 1000Base-X SFP, 1x 10/100/1000Base-T (PoE-PD)
General:	
Dimensions (HxWxD)	46x110x163mm
Number PoE ports	4
Model	DIN rail module
Type	Layer2 switch
Weight	540g
Power consumption	60W
Blower	no
Management	no
Mounting	DIN rail
PoE Power	60 W
Power over Ethernet	IEEE 802.3at
Supply voltage	PoE+
Temperature range (operation)	-40°C ~ +75°C
Scope of delivery:	
Parts supplied	manual, power cord, Mounting Bracket, PSU
Notes:	
Remarks	We recommend the use edp. number: 216568 PoE Injector NE-60PoE to ensure an interference-free function with power supply via PD port
Application	indoor
Trunk	Contact discharge 6KV, Air discharge 8KV, IEC61000-4-2, IEC 61000-6-2

Related Products



NE-60PoE|SKU: 216568

Product recommendations



SFP-1310S40|SKU: 216477



SFP-1310M40|SKU: 216478



SFP-0850M10|SKU: 216479



SFP-1310S10|SKU: 216566



SFP-0850M40|SKU: 218758



RJT-1000SFP|SKU: 219525

