



IEB-54F0028M0A

Article number: 225714

1/3" Network Camera, Day&Night, 2592x1520, H.265, Infrared, 2.8mm, PoE, IP66

1/3" Omnivision CMOS sensor	ROI (Region of interest) Hi-Stream to reduce the bandwidth
Fixed 2.8mm, Day&Night lens	
Resolution max. 2592x1520	Tampering, Defog
Compression H.265/ H.264/ MJPEG	D-WDR (Digital Wide Dynamic Range)
Cross-Web-Browsing	Framerate increase on motion detection
	Compact design, Outdoor applications, IP66

Specifications

Camera:	
Camera type	Bullet
Sensor size	1/3"
Resolution standard	4 Megapixel
Imager	CMOS, OmniVision Sensor 4689
System	True Day&Night
Sensitivity	0,1 Lux, 50 IRE
Low speed shutter	yes, automatic
Manual electronic shutter (MES)	1~1/20.000sec.
Automatic electronic shutter (ESC)	1~1/20.000sec.
Wide Dynamic Range (WDR)	D-WDR
Backlight compensation	BLC
Day/Night switching	day, night, auto
IR cut filter	switchable
White balance	automatic, manual
Signal-to-noise ratio	50dB

Video:	
Resolution	2 Megapixel Modus @ 30fps, 4 Megapixel Mode @20fps, 2592x1520 (16:9), 1920x1080 (16:9), 1280x1024 (5:4), 1280x720 (16:9), 1024x768 (4:3), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 320x240 (4:3)
Resolution max.	2592x1520
Resolution max. [#1]	VerticalView 90°/270°, 4:3, 16:9, 5:4
Stream types	1x H.265, 1x H.264, 1x MJPEG multiple
Image transmission rate max.	30 fps
Compression standard	H.264, H.265, H.264+ (Smart Stream), H.265+ (Smart Stream), M-JPEG

Lens:	
Lens type	fixed focal length
Focal length	2,8 mm
MOD (Minimum object distance)	0,3 m
Iris control	DC
Vertical angle of view	52 °
Horizontal angle of view	93 °

Features:	
Multicast compliant	yes
Motion detector	yes
Analysis functions	motion analysis, intrusion, tampering protection, Defog
Alarm processing	E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML
Audio support	no
Password protection	yes
e-PTZ support	yes
Internal storage	no
Menu languages	English, German, French, Russian, Chinese, Korean, Japanese
Privacy zones masking	Areas-ON/OFF switchable

Features:	
Remote configuration	web browser
Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG setup limited, Mozilla: MJPEG setup limited, Google: MJPEG setup limited, Edge: MJPEG setup limited
User interface	Type B (white / blue)
Mirror function	H-flip, mirror
Digital Noise Reduction (DNR)	yes

Network:	
Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour, QoS, OpenVPN

Interfaces / Inputs / Outputs:	
Video outputs	no
External connections	RJ-45, 12VDC input (DC plug), connection cable approx.40cm
Ethernet interface	10Base-T, 100Base-TX
Alarm inputs	no
Alarm outputs	no
Serial interfaces	Ethernet

General:	
Series	eneo EN-Series, Safe & Easy
Dimensions (HxWxD)	76,6x75,8x150,4mm
Illumination	infrared, 1x High Power LED 850nm
Illumination range	approx. 30m
Colour (housing)	white
Housing	outdoor
Housing material	aluminium
Weight	465g
Integrated wall mount	yes
Power consumption	5,1W
Blower	yes
Mounting	wall mount, ceiling mount
ONVIF	ONVIF Profile S
Power over Ethernet	IEEE 802.3af
Window heater	no
Protection rating	IP66
SDK	upon request
Hidden cable management	yes
Sunshield	no
Supply voltage	PoE, 12VDC
Temperature range (operation)	-20°C - +50°C
Text display	supplied
Vandalism resistant	no

Scope of delivery:	
Parts supplied	manual, bag of screws

Related Products



VT-PS12DC-10|SKU: 70543



AK-8B|SKU: 225729



AK-9B|SKU: 225730

Product recommendations



IAR-7SE1024MMA|SKU: 214460



IAM-5SE1008MUA|SKU: 214459



IAD-5SG1004MUA|SKU: 216469



IAD-5SG1008MUA|SKU: 216472




IAR-7SG1008MMA|SKU: 216473



IAR-7SG1016MMA|SKU: 216474



IAR-7SG1024MMA|SKU: 216682



eneo Site Manager|SKU: 218218

