



IED-62V2812P0B

Article number: 219549

1/2.8" Network Dome, Fixed, Day&Night, 1920x1080, Infrared 2,8-12mm, 12VDC, PoE, Indoor

1/2.8" Sony CMOS sensor	Browser-independent (IE, Edge, Safari, Firefox, Chrome)
Resolution max. 1920x1080	Triple Streaming: 2x H.264, 1x MJPEG
Varifokal 2.8-12mm Day&Night lens	Responsive web design, Supports zero configuration
Digital Wide Dynamic Range (D-WDR)	Vertical view 90° / 270° mode (H.264 only)
VCA (video content analysis)	ONVIF confirmation, PoE IEEE802.af

Specifications

Camera:		Features:	
Camera type	Dome	Audio support	no
Sensor size	1/2.8"	Password protection	yes
Resolution standard	HD 1080p	e-PTZ support	yes
Imager	CMOS, Sony, Sensor IMX322	Internal storage	no
System	True Day&Night	Menu languages	English, German, French, Polish, Finnish
Sensitivity	0,15 Lux, at F1.3, 40IRE	Privacy zones masking	Areas-ON/OFF switchable
Low speed shutter	yes, automatic	Remote configuration	web browser
Manual electronic shutter (MES)	1/25 ~ 1/10000sec.	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.	User interface	Type A (orange / grey)
Wide Dynamic Range (WDR)	D-WDR	Mirror function	mirror, flip
Flickerless function	yes	Digital Noise Reduction (DNR)	yes
Backlight compensation	BLC, HLC	Network:	
Day/Night switching	auto, day, night, extern (Sensor), night-color mode	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
IR cut filter	switchable	Interfaces / Inputs / Outputs:	
White balance	ATW-Indoor, ATW-Outdoor, manual, automatic, Fluorescent light, Light bulb, Flammes, Shade, Clear Sky	Video outputs	no
Signal-to-noise ratio	50dB	External connections	RJ-45, connection cable approx.55cm
Video:		Ethernet interface	10Base-T, 100Base-TX
Resolution	1920x1080 (16:9), 1600x900 (16:9), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)	Alarm inputs	no
Resolution max.	1920x1080	Alarm outputs	no
Stream types	2x H.264, 1x MJPEG multiple	Serial interfaces	Ethernet
Image transmission rate max.	30 fps	General:	
Compression standard	H.264, M-JPEG	Series	eneo KN-Series
Lens:		Dimensions (HxWxD)	87x113mm
Lens type	varifocal	Illumination	infrared, 24x LED 850nm
Zoom factor	4x	Illumination range	approx. 30m
Focal length	2,8 - 12 mm	Colour (housing)	white
Digital zoom	16x	Colour (bubble)	clear
MOD (Minimum object distance)	0,5 m	Housing	indoor
Iris control	DC	Housing material	plastic
Vertical angle of view	51 - 18 °	Weight	275g
Horizontal angle of view	112 - 32 °	Heater	no
DORI:		Power consumption	6W
Detection (25 px/m)	45 - 130 m	Blower	no
Observation (62 px/m)	18 - 56 m	Mounting	wall mount, ceiling mount
Recognition (125 px/m)	9 - 25 m	ONVIF	ONVIF Profile S
Identification (250 px/m)	4 - 13 m	Power over Ethernet	IEEE 802.3af
Features:		SDK	upon request
Multicast compliant	yes	Supply voltage	12VDC, PoE
Motion detector	yes	Temperature range (operation)	-10°C ~ +50°C
Analysis functions	motion detection, tampering protection, trip wire detection with counting and direction detection, Field detection, Defog	Text display	supplied
Alarm processing	E-Mail, FTP, Boost, HTTP, TCP, UDP, Onvif Event Mapping	Vandalism resistant	no
Vertical tilt range	65 °(25 ~ 90°)	Scope of delivery:	
		Parts supplied	manual, bag of screws

Related Products



VT-PS12DC-10|SKU: 70543

More product information

Smart IR technology: Automatically adjusts the IR illuminance to the ambient conditions

Product recommendations



IAR-7SE1024MMA|SKU: 214460



IAM-5SE1008MUA|SKU: 214459



IAD-5SG1004MUA|SKU: 216469



IAD-5SG1008MUA|SKU: 216472




IAR-7SG1008MMA|SKU: 216473



IAR-7SG1016MMA|SKU: 216474



IAR-7SG1024MMA|SKU: 216682



eneo Site Manager|SKU: 218218

