

ISM-32F0036M00

SKU: 234978



1/2,8" Mini Network Modul, 1920x1080, Day&Night, 3DNR, 3,6mm, 12VDC, PoE, Indoor

Main Features

Sony STARVIS 2MP Image Sensor

Resolution max. 1920x1080 (Full HD)

Video Compression Format: H.264/MJPEG

Motion Detection

Built in SD micro slot

Low Speed Shutter

2DNR, 3DNR and WDR support

PoE Cable

Lens 3.6mm (further lenses upon request)

Power Supply 12VDC (1.8W) or PoE (IEEE802.3af)

Operation Temperature -10°C - +50°C

Specifications

General:	
Dimensions (HxWxD)	35x35mm
Illumination	no
Supply voltage	12VDC, 12VDC
Text display	supplied
Camera Type	Board Camera
Housing	Indoor
Color (housing)	black
Housing material	Metal
Blower	no
Mounting	Ceiling mount, Wall mount

ISM-32F0036M00

Continuation of the specifications

Power consumption	1.8W
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-10°C ~ +50°C
Certifications	IK08
Weight	200g
DORI:	
Observe (62 px/m)	22 m
Recognize (125 px/m)	9,9 m
Identify (250 px/m)	3,6 m
Detect (25px/m)	56,6 m
Functions:	
Alarm processing	FTP
Motion detector	yes
Digital noise reduction (DNR)	yes
Menu languages	English
Mirror function	mirror, flip
Password protection	administrator & users
Privacy zone masking	Areas-ON/OFF switchable
Web browser	MS Internet Explorer vers. 9.0 or higher, Safari: MJPEG, Mozilla: MJPEG, Edge: MJPEG
Audio support	no
Internal storage	microSDHC card, microSDXC card
Analysis functions	Motion detection
Camera:	
Imager	Sony STARVIS, Sensor IMX327, CMOS, CMOS
Automatic electronic shutter (ESC)	1/30~1/30.000sec.
Flickerless function	yes
Backlight compensation	BLC, HLC
Low speed shutter	ON/OFF switchable, yes
Manual electronic shutter (MES)	1/30~1/30.000sec.
Signal-to-noise ratio	50dB
Day&Night mode	Automatic, Day, Night
White balance	Indoor, Outdoor, User defined, Push
Wide Dynamic Range (WDR)	WDR 100dB, WDR 100dB
Resolution Standard	HD 1080p
System	electronic Day&Night
Sensor size	1/2.8"
Day&Night switch	Electronic
Sensitivity	0,1 Lux at F2,5, 30 IRE
Camera type	Modul
Parts supplied:	

ISM-32F0036M00

Continuation of the specifications

Parts supplied	manual,bag of screws,mounting bracket
Network:	
Network protocols	TCP/IP,UDP,DHCP,JGMP,ICMP,HTTP,UPnP,FTP,S MTP,SNTP,DNX,RTSP,RTMP
Lens:	
Iris control	no
Focal Length	3,6 mm
Digital Zoom	no
Interfaces / Inputs/ Outputs:	
External connectors	RJ-45,connection cable approx.15cm
Alarm inputs	no
Alarm outputs	no
Ethernet interface	100Base-TX
Serial interfaces	Ethernet
Video:	
Resolution	1920x1080 (16:9),1280x720 (16:9),800x600 (4:3),704x480 (4:3),640x480 (4:3),320x240 (4:3)
Stream types	2x H.264, 1x MJPEG multiple
Video compression	H.264, M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Other	
Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Motion Detector	yes
Iris Control	no
Horizontal Angle of View	92°
Vertical Angle of View	49°
Illumination	no
Manufacturer order number	234978

Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
216472	IAD-5SG1008MUA	Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8

63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

