

KBD-NSC-100

Home | Security | Recording | Accessories

KBD-NSC-100
Network System Controller with 3-Axis Joystick and Jog Shuttle,
12VDC
Art-Nr. 74746



Main Features

Hybrid Remote Keyboard (IP & Analog Devices)
Multi Device Control (PTZ/DVR/MMX/NMS/Server,etc.)
Macro Function (up to 100 Macros)
Programmable Presets, Tours, Patterns and others
Separable Joystick for Left&Right-handed Operators
Function Mapping (up to 8 Functions)

Easy Firmware Upgrade by USB and Network
Built-in 2 Lines Character LCD Display
Two-way Audio Communication
2x USB 2.0 Interface
Integrated Web Server: 10Base-T/100Base-TX
RS-485: 2x Half-Duplex Communication (PTZ & DVR)

Specifications

Operation mode	Single operation
Audio inputs	1 (Microphone)
Audio output	1x Loudspeaker (mono/stereo, 3.5mm jack)
Joystick	3-axis proportional joystick for manual control of variable speed
Site control (direct mode operation)	Keys select cameras and monitors, operate presets, patterns, auxiliaries, and sequences. Camera functions: pan, tilt, zoom, focus, iris for fixed or variable speed control of the camera series Fastrax, Minitrax
Control functions	Macro record and play: up to 100. Function mapping: up to 8. Device control via network (Cameras, DVRs, MMX, etc.). Network camera control. Automatic device scan. Network DVR mouse control and network clip copy.
Macro function	up to 100. 4 function keys can be used as a macro shortcut.
Control functions	Selection: Device, Number (0-9, in/decremental). DVR: Jog/Shuttle, Direction, Display, Playback, Emergency (Panic, Alarm). PTZ: Joystick, Preset, Focus, Iris, Motion Control (Autopan, Tour, Pattern, Home). Advanced: Macro, Shift, 4 function buttons.
Control Interface	2x RS-485 (1x PTZ / 1x DVR). 67 different RS protocols.

KBD-NSC-100

(Continuation Specifications)

Ethernet interface	10/100-Base-TX, RJ-45
Interfaces external storage	USB File copy from DVRs remotely
USB Interface	2x USB 2.0
Remote control	Mouse control
Programming	On-screen menu
Menu languages	English
LCD display	16x2 characters
Software upgrade	Firmware upgrade (via USB and network), LCD setup, Remote setup (via PC).
Password protection	Multi level (administrators and users)
Supply voltage	5VDC (plugable PSU 100~240VAC / 50~60Hz included)
Power consumption	6watts
Colour	Black
Temperature range	0 ~+50°C
Dimensions (HxWxD)	95x377x177.6mm
Weight	1.1kg
Parts supplied	Power supply unit with power cord, Joystick connecting cable, Adaptor and accessory pack, INIT CD, Manual
Certificates	CE

