



PXD-5360F01R

Article-No.: 204276

1/2.5" Network Camera, 360°
Fisheye Lens, Day&Night,
IR-LED, H.264, 2592x1944, PoE

Mainfeatures

360° 5 megapixel day&night IP camera
25fps @ 1080p Full HD, 12fps @ 2592 x 1944
True day&night mode with IR cut filter (ICR)
Quad codec: 3x H.264 plus 1x MJPEG stream
3DNR (digital noise reduction)
Built in microphone

1/2.5" CMOS sensor
360-degree panoramic view, EPTZ, quad view
6x integral IR LED illumination
D-WDR (wide dynamic range)
Alarm recording (Micro SD card)
802.3af compliant PoE standard

Specifications

Series	eneo PXD
Resolution standard	HD 1080p
System	True Day&Night
Sensor size	1/2.5"
Imager	CMOS
Sensitivity	0,2 Lux
Sensitivity	(colour); 0,02 (B&W)
Automatic gain control (AGC)	supplied
Automatic electronic shutter (ESC)	1~1/10.000sec.
Digital Noise Reduction (DNR)	yes
Digital Noise Reduction (DNR)	3D- DNR
Low speed shutter	yes
Low speed shutter	1/1.5~1/425sec.
White balance	automatic, ATW, manual
Backlight compensation	BLC
Wide Dynamic Range (WDR)	D-WDR

Specifications (continued)

IR cut filter	switchable
Resolution max.	2592x1944
Resolution	2592x1944 (4:3), 2048x1536 (4:3), 1920x1080 (16:9), 1280x1024 (5:4), 1280x720 (16:9), 1024x768 (4:3), 800x600 (4:3), 720x576 (4:3), 640x480 (4:3), 352x288 (4:3)
Image transmission rate max.	25 fps
Privacy zones masking	5 areas selectable
Activity detection	yes
Motion detector	4 zones, ON/OFF switchable
Analysis functions	activity detection, tampering protection
Sharpness correction	selectable
Brightness	selectable
Menu languages	German, English, Spanish, French, Russian, Italian
Picture adjustments	brightness, contrast, saturation
OSD function control	OSD camera setup
External connections	RJ-45
Video outputs	no
Audio support	yes
Audio	Built-in microphone, speaker
Alarm inputs	1
Alarm outputs	1
Alarm processing	SD-card recording, FTP, E-Mail, alarm out
Internal storage	microSD card
Compression standard	H.264, M-JPEG
Stream types	3 streams H.264, 1 stream MJPEG multiple
Ethernet interface	10Base-T, 100Base-TX
Web browser	MS Internet Explorer vers. 7.0 or higher, Safari (Java), Mozilla Firefox (Java, Quick time), Google Chrome (Java)
Network protocols	TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, IPv4, IPv6
Multicast compliant	yes
Lens type	fisheye
Focal length	1,05 mm
Horizontal angle of view	180°
Digital zoom	8x
Illumination	infrared
Illumination	6x LEDs 850nm
Serial interfaces	no
Remote configuration	web browser, remote software
Password protection	yes
e-PTZ support	yes
Supply voltage	PoE, 12VDC, 24VAC
Supply voltage	(+/-10%)
Power over Ethernet	yes
Power over Ethernet	IEEE 802.3af
Heater	no
Power consumption	12W max.




Specifications (continued)

Mounting	wall mount, ceiling mount
Temperature range (operation)	-10°C ~ +50°C
Vandalism resistant	no
Housing	indoor, dome
Housing material	plastic
Colour (housing)	RAL9003
Colour (bubble)	-
Protection rating	n/a
SDK	upon request
ONVIF	yes, ONVIF Test Tool Version 11.12 (Profile S)
Certificates	CE
Dimensions (HxWxD)	149x47mm
Weight	370g
Parts supplied	remote viewer software, manual, screw set, Torx key, plug set

Optional Accessories

Image	Artikel-Nr. / Typ	Description
	ZELARIS ELEMENTS	Video Management Software, for eneo IP Cameras, max 16 cameras
	PSA-1600U	Gigabit Ethernet Switch, Layer 2, unmanaged, 16 Port, 230VAC
	PSA-2400U	Gigabit Ethernet Switch, Layer 2, unmanaged, 24 Port, 230VAC
	PSA-2400M	Gigabit Ethernet Switch, Layer 2, managed, 24 Port, 230VAC
	PNR-5216	Network Video Recorder, 16xIP, 1920x1080, 480fps, 1TB, H.264, MPEG-4, M-JPEG, DVI, D-Sub

Optional Accessories (continued)

Image	Artikel-Nr. / Typ	Description
	PNR-5116	Network Video Recorder, 16xIP, 1920x1080, 320fps, 1TB, H.264, MPEG-4, M-JPEG
	PNR-5108	Network Video Recorder, 8IP, 1920x1080, 200fps, 1TB, H.264, MPEG-4, M-JPEG
	PNR-5104	Network Video Recorder, 4IP, 1920x1080, 100fps, 1TB, H.264, MPEG-4, M-JPEG

Your partner for eneo products:

