

Video Security

Signal Processing | eneo Switchers & Amplifiers

VDA-4A

Video Signal Distributor 1 Inp., 4 Outp.
in Housing, 230VAC, Pantone Coolgray 1C

Art-No. 75101



Features

1 Input
4 Outputs
Video Bandwidth: 10 MHz (+/-3 db)
Signal-to-noise Ratio: >55 db

Integrated Signal Pre-Equalization (HF Gain)
Integrated Signal Pre-Amplification (Linear Gain)
Supply Voltage: 230 VAC / 50 Hz

Specifications

Video input	1.0 to 2.0Vp-p, (C)VBS, 75ohms, BNC
Video outputs	4x 1.0 to 2.0Vp-p, (C)VBS, 75ohms, BNC
Video signal bandwidth	0 to 10MHz +/-3db
Signal-to-noise ratio	>55db
Signal pre-equalization range (HF gain)	0 to 6.0db stepless adjustable (common for all outputs)
Distributor configuration	1 input to 4 outputs
Signal pre-amplification range (linear gain)	0 to 6.0db stepless adjustable (common for all outputs)
Internal adjustments	1 Potentiometer each for the stepless adjustment of the linear and HF gain
Tilt	</= 1% at 50Hz
Supply voltage	230VAC/50Hz
Power consumption	Approx. 3.0W
Temperature range	0°C to +50°C
Housing	Steel metal
Colour	Pantone Coolgray 1C
Dimensions (HxWxD)	44x108x135mm
Weight	Approx. 600g

VIDEOR TECHNICAL E. Hartig GmbH
Carl-Zeiss-Straße 8 · 63322 Rödermark · Germany
Telefon +49 (0) 60 74/8 88-0 · Telefax +49 (0) 60 74/8 88-100
info@videortechnical.com · www.videortechnical.com

