

# VKCD-135/HR

Home | Security | Dome Cameras | Fixed

VKCD-135/HR  
1/3" Mini Dome, Fixed, Colour, 3.7mm, 550TVL,  
12VDC

Art-Nr. 92208



## Main Features

For Wall and In-ceiling Mount  
Resolution of 550 Horizontal Lines  
Built-in Pinhole Lens F2.0/3.7 mm  
Electronic Shutter Control (ESC)

Internal Synchronization  
Easy Installation  
Supply Voltage: 12 VDC

## Specifications

Video standard	PAL
System	Colour
Sensor size	1/3"
Imager	CCD, Sony Super HAD Interline Transfer
Picture elements	440,000 752(H) x 582(V)
Synchronization	Internal
Sensitivity (at 50% video signal)	0.5Lux at F1.2
Horizontal resolution	550 TVL
Rotation range	360°
Tilt range	approx. +/-60°
Gamma correction	0.45
Low Speed Shutter	no
Digital Noise Reduction (DNR)	no
Backlight compensation	no
Wide Dynamic Range (WDR)	no

# VKCD-135/HR

(Continuation Specifications)

IR cut filter	standard
Video outputs	CVBS, 1Vp-p, CVBS, 75ohms
Lens mount	integrated lens
Lens type	fixed focal length
Lens	F2.0/3.7mm Pinhole
Aspherical technology	no
Focal length	3,7 mm
Horizontal angle of view	68°
Iris control	no
MOD (Minimum object distance)	0,1 m
Filter screw size	not available
External connections	Video (BNC), 12VDC (Cinch)
Serial interfaces	no
Temperature range (Operation)	-10° ~+50°C
Heater	no
Protection rating	IP40
Supply voltage	12VDC
Power consumption	0.72W
Vandalism resistant	no
Colour (bubble)	-
Camera fixing	no
Mounting	wall mount, flush mount
Housing	Indoor
Housing material	Aluminium
Colour (housing)	anodized silver-coloured (C-0)
Dimensions (DxH)	See drawing
Weight	120g
Certificates	CE

## Optional accessories

70535	VT-PS12DC-8	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, with DC Plug
70495	VT-PS12DC-7	Plugable PSU w. Cont. & UK Mains plug-in 100-240VAC/12VDC-1.25A, Regulated
77773	VT-PS12DCDT1	PSU 12VDC/1.0A, Regulated, Desktop Version, 1.8m Cables each w. open ends

