



VMC-8LCD-CM01B

Article number: 203450

8" (20.3cm) LCD Monitor, 1024x768, Black Metal Cabinet, 12VDC

| | |
|---|--|
| 8" (20.3cm) display screen size | Robust metal cabinet |
| PAL/NTSC auto selection | Supply voltage: 12VDC |
| Multi language on-screen menu control | Accessories: PSU, remote control unit, VGA cable |
| Resolution 800x600, 1024x768, 1152x864 px | Different ranges of application |
| CVBS and RGB input | |

Specifications

| Display: | |
|--------------------------------|---|
| Resolution | 1024x768 (4:3) |
| Synchronization | internal |
| Resolution pixels | 1024x768 |
| Contrast ratio typical | 500:1 |
| Response time typical | 50 ms |
| Brightness typical | 250 cd/m ² |
| Viewing angle vertical | 130 ° |
| Viewing angle horizontal | 140 ° |
| Screen size | 8" |
| Screen Size (cm) | 20,3 cm |
| Pixel format | 1024(H)x768(V) |
| Pixel fault class | ISO 13406-2, Class II |
| Video standard | PAL/NTSC |
| Features: | |
| Menu languages | English, German, French, Spanish, Italian, Korean, Japanese |
| Interfaces / Inputs / Outputs: | |
| Video inputs | 1Vp-p, (C)VBS, 75ohms, BNC |
| Video inputs (type) | composite (CVBS), VGA |
| Serial interfaces | no |
| General: | |
| Dimensions (HxWxD) | 178x215x36mm |
| Mount | VESA standard (4 threads M4, 75x75mm) |
| Housing material | metal |
| Housing color | black |
| Weight | 1.1kg |
| Power consumption | 10W max. |
| Supply voltage | 12VDC +/-5% (Power supply unit included), 12 ~ 24VDC |
| Temperature range (operation) | -10°C ~ +60°C |
| Scope of delivery: | |
| Parts supplied | PSU 100-240V/12VDC with power cord, VGA cable, IR remote control unit, Multiple language manual |

Related Products



VMC-LCD/WCMB-1 | SKU: 90394



LCD-ST/CM1 | SKU: 90491



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

