

## FH 7517 T

### 17" TFT monitor



### Specifications

**LCD Display:** 17,1" active matrix TFT LCD panel  
**Viewable size:** 337,92 (H) x 270,34 (V) mm / 5:4  
**Contrast ratio:** 500:1 (typ.)  
**Brightness:** 250 cd / m<sup>2</sup> (typ.)  
**Response time (tr/ta):** 15/10 ms (typ.)  
**Display colour:** 16,7 million  
**Pixel pitch:** 0,264 (H) x 0,264 (V) mm  
**Max. resolution:** 500 TV lines / 1280 x 1024  
**Horizontal frequency:** 30 K ~ 80 KHz  
**Vertical frequency:** 56 Hz ~ 75 Hz  
**Viewing angle H/V:** 176° / 176°  
**Display mode:** Video, S-Video, VGA/SVGA/XGA/SXGA, YCbCr  
**Signal connector:** Video 1,0 Vp-p, 75 Ohm / BNC in/out, audio in/out, 15-pin Mini D-Sub, YCbCr in  
**Audio speaker:** 1 W (max.)

**OSD menu:** VGA: Brightness, contrast, H-Pos., V-Pos., clock, phase, colour temp., user colour R/G/B, OSD H-Pos. / V-Pos., volume, PiP, language, recall  
Video: colour, tint (NTSC only), brightness, contrast, sharpness, H-Pos., volume, language, colour temp., scan, PiP, recall  
**Power input:** DC input: 12V / 3 A  
**Operating condition:** Temp. 0°C ~ +40°C, humidity 10-85%  
**Storage condition:** Temp. -20°C ~ +60°C, humidity 10-85%  
**Power consumption:** 50W (max.)  
**Power management:** VESA DPMS compatible (75x75mm)  
**Dimensions:** 375 (W) x 370 (H) x 170 (D) mm  
**Weight:** 5,0 kg  
**Safety:** FCC, CE (EMC/LVD), UL, CUL  
**Wall mounting accessories:** BA DW 151 / 161, BA DW 170 / 171  
**Further accessories:** BA RK 17 – 17" rack mount bracket

