



Product Code

F09401

COLOUR VDS VEO MONITOR 4,3"

Reference

9401

EAN

8424299094014

Description.

Description

Video door entry COLOUR monitor. TFT screen 4.3"

Installed in homes, lets you communicate with the outside panel, open the door and see the visitor on the built-in screen.

The **new VEO monitor** is even simpler and more functional. A synthesis that takes design and performance to their most essential expressions, in a monitor specially designed for those users who decide to take the leap into video.

A new member in the home for those seeking **comfort and ease** when communicating.

The VEO monitor is made of high-impact ABS plastic. Texturised finish for easy cleaning and ultraviolet protection to get more resistance to the light.

VEO incorporates a 4,3" colour TFT screen. Its unique handset design incorporating a magnet enables the user to put it back into

position correctly when the call is finished.

Its balanced design of pure lines is distinguishing, modern and minimal. VEO integrates in the ambience of any contemporary interior design.

VDS system:

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit.

Maximum distance from first access to last home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "The door is open, please close the door behind you".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Maximum distance from first access to last home: 200 m.

Technical Details

Call lengthener or light and bell activator: for direct connection of the call lengthener or light and bell activator in the corresponding terminals.

SURFACE installation (installed on the wall, the extra-thin profile only protrudes 23mm from the wall, 44mm with arm).

Monitor dimensions: 200 x200x44 (height-width-depth).

Details.

Product measurements (height x width x depth) mm	Weight (kg)	Packaging measurements (height x width x depth) cm	Video Door Entry system Technologie
200x200x44	0.5952	5,1x22,2x20,7	VDS

Manuals

97860_Monitor_Veo_VDS_V03_16.pdf

97891_Guia_rapida_Monitor_VEO_VDS_V05_16.pdf

Declaration of conformity

DOCF09401EN.pdf

Accessories



F03389

UNIVERSAL FRAME LARGE



F09402

VDS VEO MONITOR CONNECTOR



F09410

VEO MONITOR DESKTOP SUPPORT



F03443

VEO TELEPHONE HANDSET
W/INDUCT.LOOP