T-Series Readers

The Gallagher T-Series Reader and Terminal range provides contactless card functionality for access control management in your business.

Fast and secure access control

Utilizing the high speed RS485 HBUS protocol, Gallagher readers can offer an unparalleled access decision response time

Features and benefits

- Support for multiple card technologies including: MIFARE DESFire EV1®, MIFARE DESFire EV2®, MIFARE Plus® and MIFARE Classic®, as well as optional 125 kHz proximity and Bluetooth® wireless technology
- Field upgradeable software
- Secure reader authentication and encryption of data communications with HBUS
- Upgrade software in situ to keep your system up to date with the latest technology developments.

- Protection from extreme environmental conditions
- Environmentally friendly RoHS compliant and designed for minimal power consumption
- Backwards compatibility the readers are compatible with Cardax IV enabled hardware
- Support for custom site encryption keys
- Heartbeat monitoring for real-time reader status
- Extensive selection of mounting, and protection accessories





Gallagher T20 Terminal

With a contemporary and intuitive user interface, 3.5" color screen and large backlit keys, Gallagher's T20 access terminal is very easy to use. Crafted from high grade polymer material, the terminal has IP66 rated environmental protection, and IK08 rated impact protection making it ideal for use in harsh environments. The T20 is both an access reader and a management tool, able to read cards, accept PIN's and has the ability to interface directly with the security system to make control decisions.

Features and benefits

- Display company logo's, promotional imagery, and messaging, and enforce cardholder competencies through message display.
- Manage building facilities like heating, ventilation, or lighting with a key press.
- Arm and disarm up to 50 alarm zones distributed across any system controllers, with optional automated input isolation, and automated alarms acknowledgment.
- Display up to 200 unacknowledged alarms and 100 acknowledged alarms, and manage up to 100 inputs. An alarms only variant is available (The T20 Alarms Terminal - C300463) when reader capability is not required.

- Maintain system integrity with prompts to conduct manual system checks
- Extensive perimeter management functions.
- Multiple language support.
- Integrated rear tamper.
- Fully configurable Mimic Panel reflecting the status of up to 8 inputs, outputs, or alarm zones.



T20

Gallagher T30 Keypad Reader

Providing that vital extra layer of security, while being robust enough to withstand the harshest of conditions.

- Protection from the elements, with an environmental protection rating of IP68.
- Supports Gallagher Mobile Connect.
- A dedicated arming key with Alarm Zone status indication.
- IK09 impact protection rating.
- Surface and flush box mounting options.



T30

Gallagher T-Series Readers

Available in several thin-form shapes, black or white, MIFARE or multi tech, the contactless readers of the T-Series range provide a reader option for anywhere on site.

Features and benefits

- Strong environmental protection and impact protection.
- Contemporary design classic black and white, with both mullion or flushbox mounting variants.
- Configurable illumination and sound; where visual or audible indications may cause distraction.
- Lifetime warranty.





T15 Reader

Superior environmental protection

The robust construction of Gallagher's 115 Reader makes it perfect for deployment in environmentally challenging locations. Our comprehensive testing procedures prove the T15 delivers outstanding all-weather performance, making it the easy choice for outdoor use.

Slim form factor

Available in standard and multi-technology variants, the T15 sits easily on a mullion, and delivers reliable card reading performance when mounted on a variety of surfaces (including metal).

Gallagher also provide a number of accessories for the T-Series range including:

- Protective covers IK08 rating protects readers against vandal attacks and harsh environments
- Dress plates cover up holes left by previously installed readers, ensuring a clean finish for sites upgrading their reader and terminal hardware
- Bezels surrounds available in a variety of colors to suit decor
- Spacers enforces a space between the reader and the mounting surface, allowing installations on metal surfaces whilst preserving credential read range
- Mounting blocks allow the T20's wiring to be terminated in a tamper protected environment.

















Product Numbers

Mounting Blocks C300931

T20 Mounting Block, Side Cable Entry

C300930

Series Re	aders				
300495	T30 MIFARE Keypad Reader, Black	C300471	T15 MIFARE Reader, White	C300431	T11 Multi Tech Reader, White
C300496	T30 MIFARE Keypad Reader, White	C300470	T15 MIFARE Reader, Black	C300430	T11 Multi Tech Reader, Black
C300490	T30 Multi Tech Reader, Black	C300481	T15 Multi Tech Reader, White	C300411	T11 MIFARE Reader, White
C300491	T30 Multi Tech Reader, White	C300480	T15 Multi Tech Reader, Black	C300410	T11 MIFARE Reader, Black
C300461	T20 Multi Tech Terminal, White	C300441	T12 Multi Tech Reader, White	C300401	T10 MIFARE Reader, White
C300460	T20 Multi Tech Terminal, Black	C300440	T12 Multi Tech Reader, Black	C300400	T10 MIFARE Reader, Black
C300451	T20 MIFARE Terminal, White	C300421	T12 MIFARE Reader, White		
C300450	T20 MIFARE Terminal, Black	C300420	T12 MIFARE Reader, Black		
T20 Alarms	Terminal				
C300463	T20 Alarms Terminal, Black	C300464	T20 Alarms Terminal, White		
Γ-Series Dre	ess Plates				
C300326	T30 Dress Plate, Black, Pk 5	C300324	T15 Dress Plate, Black, Pk 10	C300321	T11 Dress Plate, Black, Pk 10
C300323	T20 Dress Plate, Black, Pk 5	C300322	T12 Dress Plate, Black, Pk 10	C300320	T10 Dress Plate, Black, Pk 10
T-Series Be	zels				
2300395	T30 Bezel, Black, Pk 5	C300296	T15 Bezel, Black, Pk 10	C300284	T11 Bezel, Black Pk 10
C300396	T30 Bezel, White, Pk 5	C300297	T15 Bezel, White, Pk 10	C300285	T11 Bezel, White, Pk 10
C300397	T30 Bezel, Silver, Pk 5	C300298	T15 Bezel, Silver, Pk 10	C300286	T11 Bezel, Silver, Pk 10
C300398	T30 Bezel, Gold, Pk 5	C300299	T15 Bezel, Gold, Pk 10	C300287	T11 Bezel, Gold, Pk 10
C300292	T20 Bezel, Black, Pk 5	C300288	T12 Bezel, Black, Pk 10	C300280	T10 Bezel, Black, Pk 10
0300293	T20 Bezel, White, Pk 5	C300289	T12 Bezel, White, Pk 10	C300281	T10 Bezel, White, Pk 10
C300294	T20 Bezel, Silver, Pk 5	C300290	T12 Bezel, Silver, Pk 10	C300282	T10 Bezel, Silver, Pk 10
C300295	T20 Bezel, Gold, Pk 5	C300291	T12 Bezel, Gold, Pk 10	C300283	T10 Bezel, Gold, Pk 10
T-Series Sp	20072				
C300318	T30 Spacer, Black, Pk 5	C300305	T12 Spacer, White, Pk 10	C300301	T10 Spacer, White, Pk 10
C300318	T30 Spacer, White, Pk 5	C300303	T11 Spacer, Writte, Fk 10	C300301	T20 Protective Cover Spacer
C300319	T20 Spacer, Black, Pk 5	C300302	T11 Spacer, White, Pk 10	C300312	T11/T12 Protective Cover Spacer
C300306	T20 Spacer, Black, Pk 5	C300303	T10 Spacer, Black, Pk 10	C300311	T10 Protective Cover Spacer
C300307	T12 Spacer, White, Pk 5	C300300	FIO Spacer, DIACK, PK 10	C300310	TTO FTOLECTIVE COVER SPACER
5500504	112 эрасы, раск, гк 10				
T-Series Pro	tective Covers				
C300271	T11/T12 Protective Cover	C300270	T10 Protective Cover	C300272	T20 Protective Cover

T20 Mounting Block, Rear Cable Entry

C300951

T15 Mounting Block, Side Cable Entry













Technical Specifications

T-Series Readers	T10	T11	T12	T15	T20	T30
Maximum Read distance - MIFARE Classic	75mm	75mm	75mm	75mm	100mm	90mm
- MIFARE DESFire EV1	50mm	50mm	50mm	35mm	95mm	50mm
- MIFARE DESFire EV2	60mm	60mm	60mm	50mm	100mm	85mm
- MIFARE Plus	30mm	30mm	30mm	25mm	65mm	35mm
- 125kHz	-	95mm	95mm	60mm	95mm	n/a
- Mobile Connect (BLE) ***	-	Configurable	Configurable	Configurable	Configurable	Configurable
Dimensions mm (H x W x D)	115 x 35 x 12	115 x 70 x 12	86 x 86 x 12	139 x 44 x23	179.5 x 95.7 x23	118 x 86 x 27
Dimensions inches (H x W x D)	4.5 x 1.4 x 0.5	4.5 x 2.8 x 0.5	3.4 x 3.4 x 0.5	5.5 x 1.7 x0.9	7.1 x 3.8 x0.9	4.6 x 3.4 x 1.1
Environmental protection	IP68 IP66					IP68
Impact rating	IK07 IK08					IK09
UV Stability	Nil structural degradation for the life of the reader [†]			ader*		
Voltage	9-16Vdc	9-16Vdc	9-16Vdc	9-16Vdc	9-16Vdc	9-16Vdc
Idle current @ 13.6Vdc - MIFARE	51mA	50mA	50mA	50mA	168mA	87mA
Idle current @ 13.6Vdc - Multi	-	80mA	80mA	81mA	157mA	87mA
Operational Temperature Range °C	-35° to + 70°C -30° to + 70°C					-35° to + 70°C
Operational Temperature Range °F	-31°F to +158°F -22°F to +158°F					-31°F to +158°F
Humidity	95% non-condensing					93% relative humidity (RH) at +40°C 97% RH at +25°C

Cable specifications (HBUS data only)					
Cat5e ⁺⁺	up to 500m				
Gallagher HBUS Cable ⁺⁺	up to 500m				
Standards Compliance	All equipment complies with FCC, CE, UL, and RCM approvals. Compliance and certification information is available on our support site or by contacting Gallagher.				

^{*} Read range may be reduced when reader is mounted on metal surfaces

 $^{^{\}rm tht} \, \text{For further information on the Mobile Connect solution, please refer to the Mobile Connect Datasheet}$

Protective Covers	T10	T11	T12	T20
Dimensions mm (H X W X D)	132 x 63 x 18	131 x 111 x 18	131 x 111 x 18	193 x 123 x 32
Dimensions inches (H X W X D)	5.2 x 2.5 x 0.7	5.2 x 4.4 x 0.7	5.2 x 4.4 x 0.7	7.6 x 4.8 x 1.3

 $MIFARE\ Classic,\ MIFARE\ Plus,\ MIFARE\ DES fire\ EV1\ and\ MIFARE\ DES fire\ EV2\ are\ registered\ trademarks\ of\ NXP\ B.V.$

©2013 Gallagher Group Ltd. Gallagher is an ISO 9001:2008 certified supplier. All rights reserved. The products described in this document are subject to continuous development and improvement so specifications and information may change without notice. System configuration, network capacities and the volume of system activity affect performance.

GALLAGHER WORLD HEADQUARTERS

Kahikatea Drive, Hamilton 3206 Private Bag 3026, Hamilton 3240 New Zealand

TEL: +64 7 838 9800 EMAIL: security@gallagher.com







REGIONAL OFFICES

New Zealand	+64 7 838 9800
Americas	+1 877 560 6308
Asia	+852 3468 5175
Australia	+61 3 9308 7722
India	+91 98 458 92920
Middle East	+971 4 5665834
South Africa	+27 11 974 4740
	. 440470044004

products and/or services provided by Gallagher Group Limite or its related companies (referred to as "Gallagher Group"). Information is indicative only and is subject to change withou notice meaning it may be out of date at any given time. Althoug every commercially reasonable effort has been taken to ensure the quality and accuracy of the information, Gallagher Group makes or representation as to its accuracy or completeness and it should not be relied on as such. To the extent permitted by law, all expres or implied, or other representations or warranties in relation to the information are expressly excluded. Neither Gallagher Group or any of its directors, employees or other representatives shall be responsible for any loss that you may incur, either directly clindrectly, arising from any use or decisions based on the information is subject to copyright owned by Gallagher Group a you may not sell it without permission. Gallagher Group is owner of all trademarks reproduced in this information. A trademarks which are not the property of Gallagher Group, a acknowledged. Copyright © Gallagher Group Ltd. All right reserved.





[†] Prolonged exposure to high UV light environments can cause plastics to discolor

⁺⁺ For further cable specifications please refer to the Gallagher Security System Technical Reference Manual