









COVERT CAMERA

MONOCHROME

BF-350/PA

● **Box file monochrome camera**



-  1/3" CCD
-  380 TV lines
-  3.0 lux sensitivity
-  Supply voltage: 12 Vdc
-  Audio output: 1V p-p

Lens options

Lens	Product Code
3.6mm pinhole	BF-350/PA
5.5mm pinhole	BF-350/PA/5.5

All lens options are the same price

- **Ideal for use in an office environment**
- **Camera and wiring completely concealed inside box enabling use as a file by unsuspecting user**
- **Specially designed connection block disconnects cabling automatically when file is removed from shelf**
- **Can be modified to contain wireless transmitter**
- **Comes with free power supply**
- **Comes with free audio capability**
- **Comes with lint-free cleaning cloth to remove grease and dirt from case and lens**


See Also:



BF-650/PA
Colour option



TH-350/PA
Thermostat monochrome camera



PI-350/A
PIR case monochrome camera

SPECIFICATION

	MOD-308/PA camera module
VIDEO Image sensor	1/3" CCD sensor, 512 (H) x 582 (V) pixels
Horizontal resolution	380 TV lines or greater
Lens options	SEE TABLE
Electronic shutter	Automatic linear shutter
Sensitivity	3.0 lux
Video output	CCIR, 1Vp-p, 75 Ohms
Supply voltage	12 Vdc ± 10%
Working temperature	-18°C to +60°C

AUDIO Microphone	Omni-directional electret
Audio output	1Vp-p, 600 Ohms
Audio bandwidth	100Hz - 10KHz, +/- 3dB

Specification and availability of products are subject to change without notice