

Series SN-40

Robust pan/tilt heads for outdoor use



Product information

Pan/tilt head, 24 VAC, for outdoor use
remote indication potentiometer for
prepositionin

- | Little angular clearance
- | Weather-proof
- | Robust, mechanical construction
- | Macrolon housing
- | Aluminium-casting housing interior
(patented construction)
- | Stainless-steel drive
- | Maintenance-free operation
- | IP-66 protection rating

Technical data

Technical specification	SN-40/24	SN-40/24PT	SN-40/230	SN-40/230PT
Max. load	20 kg			
Rated voltage/operating voltage	24 VAC	24 VAC	230 VAC	230 VAC
Power consumption	285 mA	285 mA	30 mA	30 mA
Max. panning angle	359°			
Max. tilting angle	+/- 90°			
Panning speed	6°/sec.			
Tilting speed	3°/sec.			
Drive clearance	< 0.2°			
Max. torque at rated speed	16.5 Nm (H) / 33 Nm (V) (operating torque at 50 Hz)			
Suitable for fixed position	NO	YES	NO	YES
Automatic shut-off	Internally programmable via micro switch			
Connection	7-pin plug			
Operating temperature range	-20 °C to +70 °C			
Protection rating	IP-66			
Mounting position	Standing or suspended			
Finish	C 31 coating / RAL 7032			
Weight	6.5 kg			
Compatible operating consoles	MBeg-422; MBeg/VS			
Order No.	5.20400	5.20420	5.20410	5.20430

Mounting accessories

Description	Wall console for pan/tilt heads from Series 40	Mast console for pan/tilt heads from Series 40	Mast adapter for Series 40
Type	WK/SN	MK/SN	MA/SN
Overhang	345 mm	350 mm	-
Total length	415 mm	420 mm	-
Tilting range	Up: 65°; down: 50°	Up: 65°; down: 50°	-
Max. load	Approx. 30	Approx. 25	Approx. 30
Dimensions	-	-	Ø 140 x 200 mm (H)
Weight	Approx. 2.3 kg	Approx. 3 kg	Approx. 2.3 kg
Finish	RAL 7032 (pebble grey)	RAL 7032 (pebble grey)	RAL 7032 (pebble grey)
Order No.	5.18380	5.18390	5.18400

Technical alterations reserved

GEUTEBRÜCK GmbH

Im Nassen 7-9 | D-53578 Windhagen | Tel. +49 (0)2645 137-0 | Fax-999 E-mail: info@geutebrueck.com | Web: www.geutebrueck.de