

PWR-24AC-16-14



16 Camera 24VAC 14.5Amp Power Supply




The PWR-24AC-16-14 is a CCTV power center engineered to manage/remote camera and accessory power requirements. The PWR-24AC-16-14 distribution module is designed with 16 individually fused outputs for powering up to 16 CCTV cameras and accessories. It will provide 24 Volts AC via distribution to sixteen fused outputs with a total of 14.5 Amps continuous supply current. The PWR-24AC-16-14 power center is housed in a premium lockable heavy gauge metal enclosure.

Key Features

- Convenient screw and terminal and fuse access
- AC power LED indicator
- Includes transformer and spare fuses
- Lockable heavy gauge metal enclosure
- Uses easy to find automotive style fuses

Dimensions Unit: mm (inch)



Technical Specifications

PWR-24AC-16-14

FEATURES
Convenient screw and terminal and fuse access
Power ON/OFF switch
Individual LED's for each fused output
AC power LED indicator
Double coated polyurethane finish
Multiple knockouts to accommodate various wiring configurations
Uses easy to find automotive style fuses
Includes transformer and spare fuses
Lockable heavy gauge metal enclosure

SPECIFICATIONS		
Input	115VAC 50/60 HZ; 2.7 Amps	
Output	5 Amps	
14.5 Amps 350 VA supply currents at 70°F		
Fuse	15 Amps	
Sixteen 24VAC individually fused outputs		
Unit maintains camera synchronization		
Transformers	(2) 110/24VA, 175VA	
Enclosure Dimensions	254 x 228.6 x 114.3mm (10" x 9" x 4.5")	