

# SAM-14M

## 14" Color CCTV Monitor



### Rear Panel



### Front Panel



### Dimension



### Features

- Microphone & speaker Built-in for one-way Audio
- VCR Connect for VCR Record and Play (On-Screen available)
- Horizontal Resolution 420TV Lines
- Free Voltage (90-260 VAC, 50/60Hz)
- NTSC/PAL
- Approval:UL, FCC, CE, CSA, DHHS

### Specification

	Model	SAM-14M
GENERAL	Color System	NTSC / PAL
	Power Source	90-260VAC,50/60Hz
	Power Consumption	65W
	Picture tube	14" Line Gun,Semi Tinted CRT
	Video Impedence	75Ohm BNC
	Speaker	70 x 40mm, 3W 80hm
	Operating temperature	0°C-40°C
	Operating humidity	35 %-80%
	Dimension(W x H x D)	350(W) x 320(H) x 370(D)
	Weight	About 14.0Kg
	Enclosure	Metal
Resolution	420 TV Lines	
VIDEO	Input Level	1.0 ± 0.2Vp-p,75Ω
	Output Level	1.0 ± 0.2Vp-p,75Ω
AUDIO	Input Level	RCA Jack Type 300 ± 50mVrms
	Sound Distortion	Less than 10%
	HUM	Less than 10m Vrms
	BUZZ	Less than 200m Vp-p
Control & Switch JACK & Terminal	Control Front	Rotary Volume:Tint(NTSC System only) Brightness, Contrast, Color, Volume(Speaker) Push Button : Power On/Off
	Jacks Rear	MIC & Speaker : One-Way Audio 2 BNC:Video Input/output 2 Audio RCA : Input/output

Design and specifications are subject to change without notice.