

CAMERA ACCESSORIES

| | | STH-330POV/PIV (Outdoor/Indoor Housing) | STH-320PO (Outdoor Housing) | STH-330PEV (In-Ceiling Housing) | STB-330PC (Ceiling Mount) | STB-20PF (Flange) |
|----------------------------|---------|---|--------------------------------|------------------------------------|-------------------------------|----------------------------|
| Operating Temperature | | -20°C ~ 50°C (STH-330POV / -10°C ~ 50°C (STH-330PIV) | -20°C ~ 50°C | -10°C ~ 50°C | -20°C ~ 50°C | -20°C ~ 50°C |
| Operating Humidity | | 0 to 90% RH (STH-330POV) / 0 to 90% RH (non-condensing, STH-330PIV) | 0 to 90% RH | 0 to 90% RH (non-condensing) | 0 to 90% RH | 0 to 90% RH |
| Materials | Housing | ALDC 12 | ALDC 10 | EGl 1.2T | ALDC 12 | EGl 2T |
| | Ring | ALDC 12 | ALDC 12 | ABS | N/A | N/A |
| | Dome | Poly Carbonate | Poly Carbonate | N/A | N/A | N/A |
| Antivibration / Waterproof | | IP 67 | IP 67 | N/A | N/A | N/A |
| Dimensions (WxH) | | Ø242x 284.5mm (Ø9.53" x 11.2") | Ø243 x 281mm (Ø9.57" x 11.06") | Ø235 x 188.5mm (Ø9.25" x 7.42") | Ø183 x 48.5mm (Ø7.2" x 1.91") | Ø183 x 3mm (Ø7.2" x 0.12") |
| Weight | | 3.02Kg (6.66 lb) | 1.55Kg (3.41 lb) | 890g (1.96 lb) | 1.3Kg (2.87 lb) | 300g (0.66 lb) |