

# SWT-P-81-240

8 Port PoE+ Switch



## Key Features

- Conforms to IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3af, IEEE802.3at
- Provides (8) 10/100/1000Base-TX ports and (1) 10/100/1000 Uplink port
- High back-plane bandwidth 18Gbps
- IEEE802.3x Flow control
- Plug and play operation
- Surge protection for power port and data ports
- EMI standards complies with FCC, CE class B
- 2 Year Warranty

### SWT-P-81-240

|                       |   |
|-----------------------|---|
| Fixed Port            | (8) 10/100/1000 Base-TX ports – (1) 10/100/1000 Uplink port |
| LED Indicators        | PWR, PoE, Link/Act VLAN LED                                 |
| Thermal Methods       | Built-in Noiseless Fan                                      |
| Switching Capacity    | 18G.  |
| MAC Address Table     | 4K  |
| Traffic Control       | IEEE 802.3x full-duplex flow control                        |
| <b>PoE</b>            |   |
| PoE Port              | (8) 10/100/1000 Base-TX ports                               |
| PoE Standard          | IEEE802.3af, IEEE802.3at, per port 30W                      |
| <b>ENVIRONMENTAL</b>  |   |
| Operating Temperature | 0°C~40°C - 32°F~113°F                                       |
| Storage Temperature   | -10°C~70°C - 14°F~158°F                                     |
| Operating Humidity    | 10%~90% (non-condensing)                                    |
| <b>ELECTRICAL</b>     |   |
| Input Voltage         | 100V~240V AC, 50/60Hz                                       |
| Power Consumption     | 250W  |
| <b>MECHANICAL</b>     |   |
| Dimensions (WxHxD)    | 13.5" x 1.65" x 7.2"  |
| Weight                | 5.8 lbs   |

\* Design and specifications are subject to change without notice.