




# DS-2CC192P(N)-IR1(IR3) **Analog IR Camera**



### **Key Features**

Compact design

• 1/3" Sony CCD

Minimum Illumination: 0.1Lux/F1.2 (0 Lux with IR)

• Auto white balance, auto gain control, electronic shutter control and backlight compensation

Internal synchronization

• Weather Proof: IP66 standard

## **Specifications**

#### Camera

Image Sensor Signal System Effective Pixel

Min. Illumination Electronic Shutter Speed Lens

> Horizontal Resolution Sync. System

1/3" Sony Super HAD CCD PAL / NTSC

PAL: 752 (H) × 582 (V) NTSC: 768 (H) × 494 (V)

0.1Lux @ F1.2 (0 LUX with IR) 1/50(1/60)s to 1/100,000s "-IR1" Series: 6mm "-IR3" Series: 12mm

540 TVL Internal

Video Output 1Vp-p Composite Output (75Ω

/ BNC) S/N Ratio 48 dB BLC On

### General

Operating Temperature

-10°C ~ 60°C Housing IP66 Standard

IR Distance "-IR1" Series: Up to 10 Meters "-IR3" Series: Up to 30 Meters

Power Supply 12V DC Power Consumption IR1: 3W Max. IR3: 6W Max.

Dimension IR1: 76.5mm×73mm×125.5mm IR3: 86.5mm×83mm×160mm

Weight IR1: 600 g IR3: 1000 g

www.hikvision.com 54