



H4W2PER2

Network WDR 2MP IR Rugged Mini Dome Camera






| OPERATIONAL | |
|--------------------------|--|
| VIDEO STANDARD | NTSC/PAL |
| SCANNING SYSTEM | Progressive scan |
| IMAGE SENSOR | 1/2.8" 2 Megapixel progressive CMOS |
| NUMBER OF PIXELS (H x V) | 1920 x 1080 |
| MINIMUM ILLUMINATION | 0.05lux/F1.4(color, 30IRE) 0Lux/F1.4(IR on) |
| S/N RATIO | More than 45dB |
| ELECTRONIC SHUTTER SPEED | 1/3~1/100000s |
| IR DISTANCE | Up to 30m(98ft), depending on scene reflectance |
| IR LIGHT CONTROL | Manual/SmartIR/OFF |
| IR LIGHT NUMBER | 2 |
| DAY/NIGHT | Auto(ICR) / Color / B&W |
| BACKLIGHT COMPENSATION | BLC / HLC / WDR |
| WHITE BALANCE | Auto/Natural/Street Lamp/Outdoor/Manual/ Customized Region |
| GAIN CONTROL | 0~100 |
| WIDE DYNAMIC RANGE | 120 dB |
| NOISE REDUCTION | 3D DNR |
| PRIVACY MASKING | Off / On (4 Areas, Rectangle) |
| MOTION DETECTION | Off / On (4 Zones, Rectangle) |
| REGION OF INTEREST | Off / On (4 Zones) |
| LENS | 2.7mm~13.5mm, Motorized, F1.4 |
| ANGLE OF VIEW | H:108°~30°, V:60°~18° |
| VIDEO | |
| VIDEO COMPRESSION | H.265/H.264H/Smart Codec/MJPEG (Sub Stream) |
| RESOLUTION | 1080P(1920×1080)/1.3M(1280×960)/ 720P(1280×720)/D1(704×480/576)/ VGA(640×480)/CIF(352×240/288) |
| FRAME RATE | Main Stream: 1080P(1 ~ 25/30fps) Sub Stream: D1(1 ~ 25/30fps) |
| BIT RATE CONTROL | CBR/VBR |
| BIT RATE | H.265: 12K ~ 6400Kbps H.264: 32K ~ 10240Kbps |
| NETWORK | |
| ETHERNET | RJ-45 (10/100Base-T) |
| SUPPORTED WEB BROWSERS | Internet Explorer (11.0+) |
| SUPPORTED OS | Windows® 7 32-bit/64-bit; Windows® 10 32-bit/64-bit |




| NETWORK (CONT'D) | |
|-----------------------|--|
| PROTOCOLS* | HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; DHCP; DNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS |
| INTEROPERABILITY | ONVIF Profile S/G/Q |
| MAXIMUM USERS ACCESS | 20 Users |
| SECURITY | User account and password protection HTTPS, IP Filter, Digest authentication, User access log, TLS1.2 only, AES-128/256, SSH/Telnet closed, sFTP by default, PCIDSS compliance |
| EVENT | No SD card, SD card error, Capacity warning, Network disconnection, IP conflict, Illegal access |
| MICRO SD | Up to 128 GB microSDHC card, Class 10 (not included) |
| ELECTRICAL | |
| POWER SUPPLY | DC12V, PoE (802.3af)(Class 0) |
| POWER CONSUMPTION | <9W |
| MECHANICAL | |
| DIMENSIONS | Ø122mm×88.9mm(4.80"×3.50") |
| PRODUCT WEIGHT | 0.50kg (1.10lb) |
| PACKAGE WEIGHT | 0.66kg (1.46lb) |
| CONSTRUCTION | Die-cast aluminum housing with powder coat |
| CONSTRUCTION COLOR | RAL 9003 (White) |
| ENVIRONMENTAL | |
| OPERATING TEMPERATURE | -30° C ~ +60° C (-22° F ~ +140° F) |
| RELATIVE HUMIDITY | Less than 95%, non-condensing |
| INGRESS PROTECTION | IP 66 |
| VANDAL RESISTANCE | IK10 |
| REGULATORY | |
| EMISSIONS | FCC Part 15B, EN 55032 |
| IMMUNITY | EN 50130-4 |
| SAFETY | UL 60950-1, EN 62368-1 |
| ROHS | EN 50581 |

* Some development may be required in specific user cases to support some of these protocols in the field as they mature over time.

Network WDR 2MP IR Rugged Mini Dome Camera

RECOMMENDED ACCESSORIES

| SYSTEM COMPATIBILITY | | MOUNTS AND ACCESSORIES | |
|----------------------|---|------------------------|---|
| HEN*4 | 8/16/32/64-channel Performance Series 4K NVRs (H.264 and H.265) | HQA-PM2** |  Pole Mount Adapter |
| HEN*3 | 4/8/16/32-channel Performance Series 4K NVRs (H.264 and H.265) | HQA-IC |  In-Ceiling Bracket |
| HEN*2 | 4/8/16-channel Performance Series NVRs (H.264) | HQA-BB4** |  Junction Box |
| HRHT4* | 4/8/16-channel 4 MP HQA/IP/CVBS Hybrid DVRs (H.264) | HQA-CB** |  Ceiling Mount Bracket for Pendant Mount Cap |
| | | HQA-CBE** |  Ceiling Mount Extend Bracket for HQA-CB |

| MOUNTS AND ACCESSORIES | | |
|------------------------|---|---------------------|
| HQA-RS |  | Rain Shield Bracket |
| HQA-PK** |  | Pendant Mount Cap |
| HQA-WK |  | Wall Mount Bracket |

** The HQA-BB4 must be used when installing the camera to HQA-PM2, vice versa.


The HQA-PK must be used when installing the camera to HQA-CB.

The HQA-CBE must be used with HQA-CB together.

ORDERING

| | |
|----------|--|
| H4W2PER2 | Network WDR 2MP IR Rugged Mini Dome Camera, 1/2.8" CMOS, 2.7mm~13.5mm Motorized, 2 IR LEDs, PoE, IP66, H.265/H.264/Smart Codec |
|----------|--|

DIMENSIONS



For more information

www.honeywellvideo.com

Honeywell Security

2700 Blankenbaker Pkwy, Suite 150
 Louisville, KY 40299
 1.800.323.4576
www.honeywell.com

ONVIF and the ONVIF logo are trademarks of ONVIF Inc. Honeywell reserves the right, without notification, to make changes in product design or specifications.

HSV-H4W2PER2-01-US(1118)DS-Y
 © 2018 Honeywell International Inc.

Honeywell