

PRO-WATCH® NVR SOFTWARE

Network Video Recording Solution



PRO-WATCH NVR SERVER – VERSION 6.5 OR ABOVE UP TO 64, 128 OR 256 CHANNELS	
PROCESSOR	Intel® Core™ i7-7700, 3.6 GHz or higher for up to 64 Channels, Xeon Silver 4110, 2.1 GHz or higher for 128 Channels, dual Xeon Silver 4210, 2.2 GHz or higher for 256 Channels
SYSTEM MEMORY (RAM)	Minimum 16 GB or higher for up to 64 Channels, minimum 32GB for 128 Channels, minimum 64GB for 256 Channel
OS & APPLICATION – HARD DISK DRIVE OR PARTITION	Minimum 200 GB Partition drive or separate hard drive
GRAPHICS ADAPTER	Minimum In-built Processor Graphics (GPU): Intel® HD Graphics 630 or equivalent for local client GPU rendering support
NETWORK INTERFACE	Minimum – 2 Gigabit network interface card, Recommended dual 10GbE network interface card for >800 Mbps throughput
OPTICAL DRIVE	Optional DVD-RW
VIDEO STORAGE DRIVE	Video rated or Enterprise drive, 7200 RPM SATA/SAS recommended
MONITOR RESOLUTION	Video resolution 1280x1024 pixels or higher, 32 bit
KEYBOARD/MOUSE	102-key keyboard and mouse
OPERATING SYSTEM OPTIONS	Microsoft® Windows 10, Windows 10 IoT Enterprise for Embedded Systems, Windows Server 2014 R2, 2016 R2 and 2019
DATABASE	Microsoft® SQL Server® 2019 Express is automatically installed while installing Pro-Watch NVR Server
SUPPORTED PERFORMANCE – 64-BIT WINDOWS OS	
RECORDING AND MONITORING PERFORMANCE	RAID/JBOD Video Storage with 6 GB/s SAS/SATA RAID Card: 256 channels with 7680 fps @ 4CIF/VGA or 7680 fps @ 720p HD or 7680 fps @ 1080p (4 Mbps bitrate) HD. 1-way audio for up to 256 IP channels. Network bandwidth/throughput: 1800 Mbps. Rendering performance using GPU of up to 4 1080p HD @ 20 fps / 80 fps on local client. Note: Oncam Grandeye 360 cameras are not supported with GPU rendering and use CPU rendering by default.
SERVER BASED VMD (SMART VMD) PERFORMANCE - CHANNELS SUPPORTED	RAID/JBOD Video Storage with 6 GB/s SAS/SATA RAID Card: Channels at max fps-64 ch at 1920 fps @ 4CIF/VGA or 64 ch at 1920fps @ 720p or 64 ch at 1920fps @ 1080p or total 128 Megapixel. All Channels at fps-64 ch at 1920 fps @ 4CIF/VGA or 1920 fps @ 720p or 1920 fps @ 1080p or total 128 Megapixel. Smart VMD is not recommended when more than 64 cameras are connected to the NVR
MAX VIDEO STREAMS SUPPORT	Web Client: Live – 64 streams, Playback - 32 streams. Note: Live streams consumed are per camera being viewed live and duplicate live views of the same camera in multiple or same web client instance are allowed without consuming additional streams. Playback streams consumed are per playback stream being viewed and each playback stream being viewed consumes 1 additional stream. Desktop Client: Live - 256 streams, Playback/Video retrieval sessions - 32, Sync playback - 9 streams. 256 live streams limit excludes 1 stream used per camera if SMART VMD is enabled. Maximum live streams per camera is 15 with SMART VMD enabled. Mobile App: 16 streams of 1080p HD @ 5 fps each. Note: During archival operations, maximum no of playback streams recommended from Desktop Client and Web Client is 16 streams.
ARCHIVAL PERFORMANCE	RAID/JBOD Video Storage with 12 GB/s SAS/SATA RAID Card: 64 channels @ 2.5 Mbps / 160 Mbps total archival bandwidth while recording 128 channels @ 2.5 Mbps / 320 Mbps with total bandwidth/throughput 700 Mbps
MULTI-STREAM PERFORMANCE	Support for maximum 256 streams. Support for configuring 1 preferred stream for continuous recording and 1 preferred stream for live video / motion based recording per camera, subject to overall bandwidth / throughput.

OPERATIONAL – PRO-WATCH NVR SOFTWARE	
IMAGE COMPRESSIONS SUPPORTED	MJPEG, MPEG-4, H.264, H.265
SUPPORTED HONEYWELL IP CAMERAS & ENCODERS	Supports Honeywell's Performance IP, equip® Series, 30 & 60 Series IP cameras. Refer to: https://hwl.co/hota/
SUPPORTED THIRD PARTY IP CAMERAS & ENCODERS	Refer to the Pro-Watch® NVR Compatibility on https://hwl.co/hota/ for a comprehensive list of compatible products to which this device is integrated.
AUDIO SUPPORT	1-way audio for specific IP camera models. Refer to: https://hwl.co/hota/
MAXIMUM NUMBER OF DESKTOP CLIENT CONNECTIONS	Desktop Client - 18 remote per server from 9 remote workstations + 1 local on NVR server.
SALVO LAYOUTS	Desktop Client - Full, 2x2, 1x5, 3x3, 2x8, 1x12, 4x4. Web Client - 2x2, 1x1, 1x2, 1x3. Mobile app (Phone) - 2x2, 2x4, 1x2, 1x1. Mobile app (Tablet) - 3x3, 2x2, 1x1.
PICTURE CONTROLS PER CAMERA	Sharpness, blur, brightness, contrast, hue, saturation, maintain aspect ratio, stretched, original size and picture mirror
OSD	Concealed text option
PLAYBACK CONTROLS PER CAMERA - DESKTOP CLIENT	FWD/REV Play x (1, 2, 4, 8, 16) Slow FWD/REV Play x (1/2, 1/4, 1/8)
SEARCH TYPES	Time/date timeline, time jump FWD/REV, bookmarks, calendar preview, film strip, event search and SMART Motion Search
RECORDING SCHEDULE	Continuous and event based with H/M/D and holiday and exception days
RECORDING METHODS PER CAMERA	Continuous, event-based and user activated
LIVE SETTINGS PER CAMERA	Compression format, resolution and frame rate
RECORDING SETTINGS PER CAMERA	Same as live or reduced frame rate
CLIP FORMAT	Honeywell MPVC and encrypted SMPVC playable with standalone Pro-Watch Clip Player for faster and secure exports. WMV with digital certificate for authentication playable with Windows media player. ASF for faster exporting of longer than an hour backup clips in native compression format.
VIDEO CLIP AUTHENTICATION	Digital signature, verification tool provided
MOTION DETECTION LOCATION	Camera based for supported models or Server based (Smart VMD) for all models (except 360 fisheye/panomorph views)
EVENT RECORDING	Pre- and post-duration setting
OPERATOR REPORTING	Per user, configurator, session and viewer
EVENT REPORT	Per camera or recorder events
OPERATORS	1024

PRO-WATCH® NVR Software

ORDERING		
PRO-WATCH NVR SOFTWARE		SOFTWARE SUPPORT AGREEMENTS FOR PRO-WATCH NVR
PWNVRSW256	Pro-Watch NVR Software – Base Software and License for 256 Channels	SSAPWNRCH Annual Software Support Agreement – Pro-Watch NVR System with VMS support included, Per Channel.
PWNVRSW128	Pro-Watch NVR Software – Base Software and License for 128 Channels	
PWNVRSW96	Pro-Watch NVR Software – Base Software and License for 96 Channels	SSA24PWNRCH Annual 24/7 Software Support Agreement – Pro-Watch NVR System with VMS support included, Per Channel
PWNVRSW64	Pro-Watch NVR Software – Base Software and License for 64 Channels	
PWNVRSW32	Pro-Watch NVR Software – Base Software and License for 32 Channels	
PWNVRSW16	Pro-Watch NVR Software – Base Software and License for 16 Channels	SSAEUPWNRCH Annual End User 24/7 Software Support Agreement – Pro-Watch NVR System with VMS support included, Per Channel
PWNVRSW8	Pro-Watch NVR Software – Base Software and License for 8 Channels	
PWNVRSW4	Pro-Watch NVR Software – Base Software and License for 4 Channels	
PRO-WATCH NVR SOFTWARE – UPGRADE LICENSES		
PWNVRSW1UP	Pro-Watch NVR Software – 1 Channel License Upgrade to add support for up to 128 Channels per NVR	
PWNVRSW4UP	Pro-Watch NVR Software – 4 Channel License Upgrade to add support for up to 128 Channels per NVR	
PWNVRSW8UP	Pro-Watch NVR Software – 8 Channel License Upgrade to add support for up to 128 Channels per NVR	
PWNVRSW16UP	Pro-Watch NVR Software – 16 Channel License Upgrade to add support for up to 128 Channels per NVR	
PWNVRSW32UP	Pro-Watch NVR Software – 32 Channel License Upgrade to add support for up to 128 Channels per NVR	
PWNVRSW64UP	Pro-Watch NVR Software – 64 Channel License Upgrade to add support for up to 128 Channels per NVR	

For more information
www.security.honeywell.com

Honeywell Commercial Security
 715 Peachtree St. NE
 Atlanta, GA 30308
 1.800.323.4576
www.honeywell.com

ONVIF and the ONVIF logo are trademarks of ONVIF Inc. Honeywell reserves the right, without notification, to make changes in product design or specifications.

HSV-PWNVRSW-05-US(0620)DS-Z
 © 2020 Honeywell International Inc.

