

VISTA 12



Hybrid Expandable Control Panel

The new Vista 12 intruder panel offers an extensive feature set at a remarkable competitive price. This hybrid panel offers 22 zones in total of which 16 zones can be wireless. Arming/disarming can be performed wireless by keyfobs. For controlling external equipment the Vista 12 is equipped with 2 outputs. These can be extended with max. 4 programmable relay-outputs or a X10 transmitter that can

drive up to 4 X10 modules. This panel even gives you the possibility to define your own zone functions. Last but not least we should mention that you will find 4 programmable keys on the keypads. Each can be individually programmed to e.g. switch on a lamp, open the garage door or arm the system while bypassing specific zones.

Features:

- Complies to EN 50131-1 and TS 5013-3 Grade 2, Class II
- Complete intruder panel
- Expandable with wired or wireless zones
- Can be divided in 3 sub-systems
- Keypads with 4 programmable keys
- Up & Downloading/Remote service through Compass software
- 16 User codes with individual authorisation levels
- 8 Schemes for limiting access, relay-outputs or automatic arming/disarming
- Integrated analogue dialler
- X10 compatible
- Activity monitoring

VISTA 12

Hybrid Expandable Control Panel

Specifications:

Feature	
No. of Zones	6/22
Max. wireless zones	16
Doubling zones	6
Zone functions	23
Self-defined zone functions	4
No. of keyfob	4
No. of keypads	8+2 6270
No. of partitions	3
Outputs (relay or X10)	2/6
Output functions	24
Automatic arm/disarm times	8
Event memory	254

Software:

Designed for installers, this Compass software allows you to up- or download the programming of the Vista 12 panel from a remote location (through telephone lines) or locally. It is also possible to service the panel with this software. Compass contains a database to store each of your programmed VISTA panels. The CIA-EU modem is fully compatible with the Compass software.

Product versions:

Version	Languages
Vista 12B	English, German and Dutch
Vista 12C	English, Hebrew, Canadian-French and Russian
Vista 12D	English, Spanish, Italian and Portuguese

Honeywell Security & Custom Electronics

Newhouse Industrial Estate, Motherwell,
Lanarkshire, ML1 5SB UK
Tel +44 (0)1698 738200
Fax +44 (0)1698 738300
Literature +44 (0)870 240 3387
www.honeywell.com/security/uk/intruder

Honeywell Security & Custom Electronics

Network 121, 1446 WV Purmerend
The Netherlands
Tel +31 (0) 299-410200
Fax +31 (0) 299-410201
www.honeywell.com/security/nl

Peripherals:

The Vista 12 is supported by a wide range of ECP-bus peripherals:

6148 ICON

- LCD display with icons
- Icons on keypad

6164 ICON

- 2 x 16 Alphanumeric LCD display
- Icons on keypad;
- 4 zones and one relay output on board

6160RFH

- 2 x 16 Alphanumeric LCD display;
- Icons on keypad;
- 868 MHz. RF-receiver on-board

6270

- B&W graphic touch screen keypad
- Menu-driven prompts
- Built-in message centre

4219

- 8 zone expansion module
- Complete with housing

4229

- 8 zone + 2 relay expansion module
- Complete with housing

4204

- 4 relay expansion module
- Complete with housing

5882H

- 868 MHz. RF-receiver for 58xxH transmitters
- Complete with housing

5882EU-HS

- 868 MHz. RF-receiver for Domonial transmitters
- Complete with housing

Domonial wireless (868 MHz.):

TCM800HF

- Panic button (1 button)
- Including transmission LED

TC805HF

- 4 button keyfob
- 5 Functions

DTO800HF

- Smoke detector
- Combined optical/fixed temperature/rate-of-rise

DOD800GY

- Magnetic contact
- Extra zone input

BVA800HF

- Glassbreak detector
- Acoustical, omnidirectional

IRX800GY

- PIR sensor (9 x 10m)

IR800PIGY

- PIR sensor (12 x 12m)
- Pet immune

CLI810HF

- Keypad

CSK800HF

- Keypad
- Including TAG reader

Honeywell reserves the right to alter the specification of products without prior notice.

Honeywell

To reorder this literature,
call +44 (0)870 240 3387 quoting ref:
HSCE-VISTA12-01-EN(0206)DS-C
February 2006
© 2006 Honeywell International Inc.